

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; & S. 36, T27-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 12 Page 4967)

Set ¼ sec. post, from which
A cedar, 6" dia., bears S.5°W., 8 lks.
A cedar, 6" dia., bears N.4°E., 7 lks.

Douglas Co. Surveyors Office - Milo Godfrey - April 1964 -
C.S. File 53/33-68

Not found.

BLM resurvey by Boyd W. Peterson, under Group #1480, Surveyed
July 1989/May 1990 - (DCSO records Vol. 50 Page(s) 18831-32)

Point for the ¼ sec. cor. of secs. 31 and 36, at
proportionate distance; there is no remaining evidence of the
original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22
ins. in the ground, with brass cap mkd.

T 27 S

¼
R 4 W | R 3 W
S 36 | S 31

1989

from which

A fir, 4 ins. diam., bears S. 31° E., 12½ lks. dist.,
mkd X BT.

A fir, 6 ins. diam., bears N. 87° W., 26 lks. dist.,
mkd. ¼ S36 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the
stainless steel post.