


TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 100241

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 25 only; T27-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2189 surveyed June/Sept 2008 - (DCSO records Vol. 57 Page 22487)

Point for the 1/4 sec. cor. of sec. 25 only, T27S R4W determined at midpoint latitudinally bet. the cor. of secs. 25, 30, 31, and 36, and the closing cor. of secs. 24 & 25. Set a stainless steel post, 28" long, 2 1/2" dia., 23" in the ground, with brass cap mkd.



from which

- A fir, 4" dia., bears S.67 3/4°W., 19.4 ft., mkd. 1/4 S25 BT.
- A fir, 6" dia., bears N.35 1/4°W., 28.3 ft., mkd. 1/4 S25 BT.

Ken Hoffine - For: Lone Rock Timberland Co. & Seneca Jones Timber Co. - July 2012 - M164-13

Found - The quarter corner for section 25 only T27S R4W bears N.0°19'22"E., 40.76 ft (from the W 1/4 cor. of sec. 30 only, T27-3, as per record, the BTs for the quarter corner for section 25 only are:
6" Fir bears S.67 3/4°W., 19.4 as per record visible scribing and tag
8" Fir bears N.35 1/4°W., 28.8 ft (rec. N.35 1/4°W., 28.3 ft) visible scribing and tag the corners lie on flat ridge sloping upward to the north with 15 year old reprod to the west and small meadow and scattered timber to the east