

PRIMARY CORNER DESCRIPTION Sec Cor to 19 & 30 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 12 Page 4967)

Set post cor. to secs. 24, 25, 19 and 30, from which
A Fir 15" dia. bears N.27°E., 23 lks. dist.
A Fir 14" dia. bears S.76°E., 15 lks. dist.
A Fir 15" dia. bears S.78°W., 20 lks. dist.
A Fir 8" dia. bears N.67°W., 15 lks. dist.

GLO Resurvey by Elmer F. Strickler under Special Instructions
dated Jan. 22, 1917 Contract #36 dated March 14, 1917
(DCSO Records, Volume 12 Pages 5031-2)

Apportioned distance. Set a granite stone, 14x7x7 ins. 10" in
the ground for the cor. of secs. 19 and 30, mkd. with 2
notches on S. and 4 notches on N. edge; from which
A Fir 30" dia. bears N.67°E., 9 lks. mkd. T27S R3W S19 BT
A Fir 32" dia. bears S.6°15'E. 43 lks mkd T27S R3W S30 BT
This cor. is 85 ft. below the summit of Lane Mountain.

Milo E. Godfrey, Deputy Co. Surv. - Wm. Stoffel, Darby; Stone
and Halterman - Oct. 1963 - C.S. File 53/33-8

Found - Granite (?) rock as called for in Gov't notes, 2
notches on S. and 4 notches on N. sides.
36" Fir S.6¼°E., 28.4 ft., has been opened
previously, good scribing visible "T27-3". Tree
alive & in good condition.
42" Fir N.67°E., 6.0 ft. Good axe scar visible. Did
not open.

Set brass cap alongside rock mkd: County Surveyors Office,
1963 T27S R4W | S19 R3W
S30

Did not mark any new bearing trees.

Fd. Ok by K Hoffine 3/2007 - M152-54

BLM Dependent resurvey by A Bert Skeesick, Cadastral Surveyor
and Robert H. Browning, Survey Tech, under Group No. 2189
surveyed June/Sept 2008 - (DCSO records Vol. 57 Page 22488)

The cor. of secs. 19 & 30 only, on the W. bdy. of the Tp.,
perpetuated by Godfrey, in 1963, monumented with an iron
post, 1¼" dia., firmly set, projecting 4" above the ground
(buried alongside of which is the orig. stone, 14x7x7", with
2 notches on the S. edge and 4 notches on the N. edge), with
brass cap (properly) mkd. continued next page

TOWNSHIP 27 RANGE 04 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor to 19 & 30 only, (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of bearing trees mkd. by Strickler
A fir, 46" dia. bears N.67°E., 5.9 ft. with a healed blaze
A sawed fir stump, 36" dia., bears S.6¼°E., 28.4 ft., with
no marks visible.
and a new bearing tree
A fir, 9" dia., bears S.22¼°E., 20.2 ft., mkd. T27S R3W
S30 BT.