

PRIMARY CORNER DESCRIPTION Closing Cor. for Secs. 24 & 25, T27-4

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
 (DCSO Records, Volume 12 Page 4967)

 Set post cor. to secs. 24, 25, 19 and 30, from which
 A Fir 15" dia. bears N.27°E., 23 lks. dist.
 A Fir 14" dia. bears S.76°E., 15 lks. dist.
 A Fir 15" dia. bears S.78°W., 20 lks. dist.
 A Fir 8" dia. bears N.67°W., 15 lks. dist.

Resurvey by Elmer F. Strickler, under Special Instructions
 dated Jan. 22, 1917 - (DCSO records, Volume 12 Page 5092)

 Intersect the W.bdy. of T27S R3W., N.0°12'E., 1.26 chains
 from the cor. of secs. 19 and 30. At the point of
 intersection, set an Iron post 3 ft. long 2" dia. 24" in the
 ground, for closing cor. of secs. 24 and 25, with brass cap
 mkd.

 T27S
 R4W|R3W
 CC S24|S19
 S25|

 1917 from which
 A Fir 32" dia. bears S.31°45'W., 47 lks. dist. marked
 T 27 S R 4 W S 25 C C BT.
 A Fir 18" dia. bears N.65°W., 72 lks. dist. marked
 T 27 S R 4 W S 24 C C BT.
 This cor. is 290 ft. above the creek.

Milo Godfrey, Dep. Co. Surv.- Stoffel; Darby; Stone; Halterman
 October 1963 - C.S. file 53/33-7

 Found - Brass cap set in 1917 survey, still firmly set.
 38" Fir S.31¼°W., 31.0 ft. Very plain axe scar
 visible. Tree alive.
 Dead and rotting Fir snag N.65°W., 47.5 ft., shows
 good scar.
 New BT - 40" D.Fir N.77½°W., 67.8 ft. mkd: T27S R4W CC S24 CS
 BT.

Harvey Christensen - June 7, 1999, Recorded 11/13/2001 - C.S.
 File 65/40-3

 Found - ½" dia. GLO brass cap on 2" iron pipe, protruding
 5" above ground level slightly tilting to the NW
 38" D.Fir S.34°W., 32.0' to ctr. with healed blaze.
 39" D.Fir N.77½°W., 67.8' to ctr. with healed blaze.
 Badly decayed Fir snag 8' high N.65°W., 47.5'
 continued next page

PRIMARY CORNER DESCRIPTION Closing Cor. for Secs. 24 & 25 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>New - 32" D.Fir N.47°E., 36.0' to ctr. blazed & scribed "X" at breast height & "BT" at base. 36" D.Fir, sawed stump, 4' high set bridge spike at NW edge of top of stump, S.45°E., 33.1' to spike. Note - The tilted monument is about. 0.10' NW'ly from vertical position.</p>
<p>Fd Ok by D Edwards, 4/2006 - M150-39 Fd. Ok by K Hoffine 3/2007 - M152-54</p>
<p>BLM Dependent resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2189 surveyed June/Sept 2008 - (DCSO records Vol 57 Pages 22488-9) ----- The closing cor. of secs. 24 & 25, perpetuated by Godfrey, in 1963, further perpetuated by Christensen, in 2001, monumented with an iron post, 2" dia., firmly set, projecting 4" above the ground, with brass cap (properly) mkd. from which the remains of the orig. bearing trees A fir, 38" dia., bears S.31¼°W., 31.0 ft., with a healed blaze. A fir snag, size indeterminate, bears N.65°W., 47.5 ft., with a healed blaze. and a bearing tree mkd. by Godfrey A fir, 39" dia., bears N.77¼°W., 67.6 ft., with a healed double blaze. and the remains of bearing trees mkd. by Christensen A fir, 32" dia., bears N.45½°E., 35.6 ft., with axe mark X in the bark and fragmentary scribe marks visible on a partially healed blaze. A sawed fir stump, 39" dia., bears S.48¼°E., 32.6 ft., with bridge spike driven into top, with no marks visible.</p>