

PRIMARY CORNER DESCRIPTION Sec cor 7 & 18; 12 & 13 of T27-4

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
 (DCSO Records, Volume 12 Page 4968)

 Set post cor. to secs. 12, 13, 7 and 18, from which
 A Laurel 4" dia. bears N.53°W., 9 lks. dist.
 A Laurel 5" dia. bears N.85°E., 27 lks. dist.
 A Laurel 3" dia. bears S.15°E., 9 lks. dist.
 A Laurel 3" dia. bears S.10°W., 23 lks. dist.

Resurvey of Portion E. Bdy of T27-4 by Elmer F. Strickler
 under Contract #36 dated March 14, 1917 and Special
 Instructions dated Jan.22, 1917 (DCSO records, Volume 12
 Page 5034)

 At Apportioned distance, Set an iron post, 3 ft. long, 2"
 dia., 24" in the ground, for cor. of secs. 7, 12, 13, and 18,
 with brass cap marked:

T27S	
R4W	R3W
S 12	S7
S 13	S18
1917	

1917 from which

A Fir 40" dia. bears N.17°E., 17 lks. dist. mkd. T27S
 R3W S7 BT.
 A Fir 8" dia. bears S.16°45'E., 61 lks. dist. marked T27S
 R3W S18 BT.
 A Fir 30" dia. bears S.58°W., 43 lks. dist. marked T27S
 R4W S13 BT.
 A Fir 12" dia. bears N.54°W., 46 lks. dist. marked T27S
 R4W S12 BT.

This corner is on a spur sloping NE.

Milo Godfrey, Doug. Co. Surveyor, etal - October 1963 - C.S.
 File 53/33-22

 Found - I. Pipe with brass cap set in 1917, in mound of large
 rocks.
 44" Fir N.17°E., 11.2 ft., shows very plain axe
 scar, tree alive.
 48" Fir S.58°W., 28.4 ft., shows very plain axe scar
 tree alive.
 Fir stump S.16¼°E., 40.3 ft., scar visible.
 23" Fir N.54°W., 29.5 ft. (Rec. 30.4 ft.) scar not
 visible. Reblaze and rescribe this tree, (in
 wood) "T27S R4W S12 CS BT"
 New BT - 10" D.Fir S.41°E., 34.0 ft. mkd: T27S R3W S18 CSBT

continued next page

PRIMARY CORNER DESCRIPTION Sec. cor. 7 & 18; 12 & 13 of T27-4


Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found and tied in 1958 BLM resurvey, DCSO records, Volume 29 Page 12408)

Found OK, Burton Holt, March 1982, M 91-37
Found OK, DCSO, Oct. 31, 1989, C.S. File 64/3-1

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1925, surveyed July/Dec. 2000 - (DCSO rec. Vol. 53 Page(s) 20526-7)

 (Condition report)
 The cor. of secs. 7, 12, 13, & 18, perpetuated by Godfrey, Douglas County Deputy Surveyor, in 1963, monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, along the E. side of which is a mound of stone, 4 ft. dia., 1 ft. high, with brass cap mkd.



from which the remains of the bearing trees mkd. by Strickler
 A fir, 43" dia., bears N.17°E., 11.2 ft., with a healed blaze.
 A sawed stump, 12" dia., bears S.25°E., 40.3 ft., with a healed blaze. (Record, S.16°45'E.)
 A fir, 46" dia., bears S.58°W., 30.0 ft., with a healed blaze. (Record, 28.4 ft.)
 A fir, 26" dia., bears N.54°W., 30.4 ft., with a healed blaze.
 and bearing tree mkd. by Godfrey
 A fir, 43" dia., bears S.41°E., 34.0 ft., with a healed blaze.
 Corner lies 2 ft. N. of end post of a barbed wire fence which extends North.

From this cor., the Bureau of Land Management Geodetic Control Station No. EC 41301 at latitude 43°13'10.992"N., longitude 123°06'37.843"W. (NAD 1983 (91)), determined by the NAVSTAR Global Positioning System, bears S.7°34'44"W., 3031.55 ft. (mean bearing and sea level distance), monumented with an aluminum cap, 3¼" dia., firmly set, flush with the ground, mkd. EC 41301 GPS 2000.

continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. cor. 7 & 18; 12 & 13 of T27-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Retracement & rehabilitation by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2300 surveyed March 2008 - (DCSO records 2009 BLM Plat & Vol. 56 Page 21838)

The cor. of secs. 7, 12, 13, & 18 on East bdy of the TP(T27-4) monumented with an iron post, 2" dia., firmly set, projecting 11" above the ground with brass cap (properly) mkd from which the remaining BTs mkd. by Strickler, reported by Skeesick

A fir, 43" dia., bears N.17°E., 11.2 ft. with a healed blaze.

A fir, 47" dia., bears S.58°W., 30.0 ft. with a healed blaze.

A fir, 28" dia., bears N.54°W., 30.4 ft. with a healed blaze.

and BT mkd. by Godfrey, reported by Skeesick

A fir, 20" dia., bears S.41°E., 34.0 ft. with a healed blaze. (Rec. 43" dia.)

The geodetic position shown hereon was determined by a tie utilizing dual frequency carrier phase GPS receivers relative to the National Spatial Reference System. (NAD 1983 (COR96))
Latitude: 43°13'40.68"N Longitude: 123°06'32.46"W