

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 31 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Sam C. Flint, contract #454, dated June 19, 1882 - (DCSO records Vol. 12 Page(s) 4975)

Set Laurel post 3 ft. long, 4" sq., for ¼ sec. cor. mkd. S C ¼ on N. face, from which

A Laurel 6" dia., bears N.70°W., 25 lks. dist. mkd. S C ¼ S BT.

A Fir 30" dia., bears S.45°E., 130 lks. dist. mkd. S C ¼ S BT.

BLM resurvey by Boyd W. Peterson, under Group #1480, Surveyed July 1989/May 1990 - (DCSO records Vol. 50 Page(s) 18829-30)

The standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

SC

T 27 S R 3 W

¼ S 31

1989

from which

A fir, 23 ins. diam., bears N. 69½° W., 67 lks. dist., mkd. X BT.

A fir, 15 ins. diam., bears N. 4° W., 32 lks. dist., mkd. ¼ S31 SC BT.

No suitable trees available to the NE. due to fire.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, a corner established by person(s) unknown, bears N. 89° 43' 00" E., 0.205 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 24 ins. above ground.

Found OK by T. Baker, May 2001 - M138-15