

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5020-1)

 Set cedar post, 3 ft. long, 3" sq., firmly in the ground for 1/4 sec. cor. mkd 1/4 S on N & S faces, from which
 A fir, 30" dia., bears N.20°E., 4 lks., mkd: 1/4 S BT.
 A fir, 12" dia., bears S.28°W., 22 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - John Powell - Wm. Stoffel - Sept 1962 - C.S. File 49/28-14

 Found - Orig. 30" now 43" fir snag N.20°E., 2.6 ft. shows good bark scribing.
 Orig. SW BT not found.
 Note - Logging road is 15 ft E & 15 ft. S of corner.
 Set - 3/4" Iron rod at corner.
 New BTs- 9" cedar bears N.72°W., 34.6 ft. scribed 1/4 S30 CS BT
 5" R.Fir bears N.32°E., 14.7 ft. scribed 1/4 S30 CS BT

BLM dependent resurvey by Boyd Peterson, Cadastral Surveyor, under Group #1480, surveyed July 1989/May 1990 - (DCSO records Vol. 50 Page(s) 18838-9)

 The 1/4 sec. cor. of secs. 30 & 31, perpetuated and recorded by Byron, in 1962, monumented with an iron rod, 3/4" dia., firmly set, projecting 6" above ground, from which the remains of an original bearing tree:
 A fir snag, 31" dia., bears N.20°E., 8 lks., no marks visible. (Record, 4 lks.)
 and bearing trees mkd. by Byron
 A hemlock 13" dia bears N.29 1/4°E. 22 lks w/healed dbl blaze
 A cedar, 14" dia bears N.73 1/4°W. 52 lks w/healed, dbl blaze
 At the corner point
 Set a stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, directly over the iron rod, with brass cap mkd.
 T27S R3W
 1/4 S 30
 S 31
 1989
 from which a new bearing tree
 A fir, 13" dia., bears S.36°W., 75 lks., mkd. 1/4 S31 BT.
 Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
 From this point, USC & GS triangulation station "LANE 1953," bears N.47° 47'56"W., 91.649 chs., monumented with a brass tablet, 3" dia., cemented flush in a 10" dia. concrete cylinder, projecting 6" above ground, mkd. USC&GS LANE 1953 and a triangle.

Cont.

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ken Hoffine - For: Lone Rock Timberland Co. & Seneca Jones
Timber Co. - July 2012 - M164-13

Found - 1989 BLM cap 6" above ground
Fir snag bears N.20°E., 5.3 ft as per record no
visible marks
15" Hemlock bears N.29½°E., 14.5 ft as per record
healed face and tag
19" Cedar bears N.73°W., 34.2 ft (record N.73¼°W.,
34.32 ft) healed face and tag
16" D.Fir stump bears S.36½°W 49.3 ft (record
S.36°W., 49.5 ft) no marks
Corner lies on west edge of dirt road cut bank and approx. 75
ft west of rock road