

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor Secs 18 & 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5025)

Set laurel post, 3 ft. long, 3" sq., firmly in the ground for 1/4 sec. cor. mkd 1/4 S on N & S faces, from which
A laurel, 16" dia., bears N.4°W., 22 lks., mkd: 1/4 S BT.
A fir, 36" dia., bears S.35°W., 59 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Garry L. Moore, Surveying Technician, under Group #1416, surveyed Oct. 1987 - March 1988 - (DCSO records Vol. 48 Page(s) 18594-5)

Point for the 1/4 sec. cor. of secs. 18 & 19, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 1/2" dia., 24" in the ground with brass cap marked:

T27S R3W
1/4 S 18
 S 19
1987

from which
A burned fir snag, 18" dia., bears N.1 1/2°E., 26 lks., mkd: 1/4 S18 BT.
A burned fir snag, 14" dia., bears S.60°E., 20 lks., mkd: 1/4 S19 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.