



TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- A cedar 18" dia. bears S.85°W., 114.5 ft. scribed "¼ S 18 CS BT"

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #1925, surveyed July/Dec. 2000 - (DCSO rec. Vol. 53 Page(s) 20528-9)

-----  
The ¼ sec. cor. of secs. 7 & 18, perpetuated by Monrean, in 1975, monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Corbin  
A root hole, bears S.8°W., 51.8 ft., with decayed trunk lying alongside, no marks visible. (Record, S.6°W., 57.4 ft.)  
A cedar, 27" dia., bears N.32°W., 95.7 ft., with a healed blaze. (Record, N.35½°W.)  
and a bearing tree mkd. by Monrean  
A cedar, 30" dia., bears S.85°W., 114.5 ft., with a healed blaze.  
and two new bearing trees  
A fir, 12" dia., bears N.49¼°E., 16.6 ft., mkd. ¼ S7 BT.  
A fir, 10" dia., bears S. 17¾°W., 30.8 ft., mkd. ¼ S18 BT.

BLM Retracement & rehabilitation by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2300 surveyed March 2008 - (DCSO records 2009 BLM Plat & Vol. 56 Page 21840)

-----  
The ¼ sec. cor. of secs. 7 & 18, monumented with an iron post, 2½" dia., firmly set. projecting 2" above the ground, with brass cap (properly) mkd. from which the remaining BT mkd. by Corbin  
A cedar, 34" dia., bears N.32°W., 95.7 ft. with a healed blaze.  
and a BT mkd by Monrean, in 1975, reported by Skeesick  
A fir, 14" dia., bears N.49¼°E., 16.6 ft. with a healed blaze.  
A fir, 11" dia., bears S.17¾°W., 30.8 ft. with a healed blaze.