

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 140540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #1925, surveyed July/Dec. 2000 - (DCSO rec. Vol. 53 Page(s) 20533)

Point for the center ¼ sec. cor. of sec. 7, at the intersection with the E and W centerline.

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, with brass cap mkd. T 27 S R 3 W

C 1/4

S 7

2000

from which

A fir, 15" dia., bears N.89¾°W., 38.2 ft., mkd. C¼ S7 BT.

A cedar, 12" dia., bears N.2°W., 49.4 ft., mkd. C¼ S7 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor., a point unofficially established during the course of a 1975 administrative survey by Roseburg District Office, BLM, bears N.85°26'55"W., 3.40 ft., monumented with a steel pipe, 1¼" dia., firmly set, projecting 18" above ground. Remove the steel pipe and deposit it inside the stainless steel post.