

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by A.R. Flint & L.L. Williams, Under Contract #151, dated May 23, 1871 (DCSO records Vol. 12 Page(s) 4973)

Set post for ¼ sec. cor. from which
A hemlock, 6" dia., bears N.50°W., 8 lks.
A hemlock, 8" dia., bears N.30°E., 12 lks.

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12440-1)

Point for the ¼ sec. cor. of secs. 6 & 7, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 26" in the ground with brass cap marked:
T27S R3W
¼ S 6
 S 7
 1958

from which
A fir, 6" dia., bears N.36°E., 44 lks., mkd: ¼ S6 BT.
A fir, 7" dia., bears S.71°W., 8 lks., mkd: ¼ S7 BT.

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #1925, surveyed July/Dec. 2000 - (DCSO rec. Vol. 53 Page(s) 20531-2)

The ¼ sec. cor. of secs. 6 & 7, monumented with an iron post, 2½" dia., firmly set, flush with the ground, with brass cap (properly) mkd.
from which the remains of a bearing tree mkd. by Corbin
A fir snag, 12" dia., 10 ft. high, bears S.71°W., 5.3 ft., with a healed blaze.
and two new bearing trees
A fir, 9" dia., bears N.75°E., 9.4 ft., mkd. ¼ S6 BT.
A fir, 7" dia., bears S.24¾°E., 11.5 ft., mkd. ¼ S7 BT.