

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by S.C.Flint, Under Contract #454, dated June 19, 1882 (DCSO records Vol. 12 Page(s) 4975)

Cor. to secs. 31 and 32. Set a post 4 ft. long, 4" sq., firmly in the ground for standard cor. mkd. S C T27S R3W on N.; S32 on E.; and S31 on W. faces with 1 notch on W. and 5 notches on E. faces, from which

- A Laurel 18" dia., bears N.75°E., 27 lks. dist. mkd. T27S R3W S32 BT.
- A Laurel 16" dia., bears N.40°W., 56 lks. dist. mkd. T27S R3W S31 BT.
- A Laurel 20" dia., bears S.3°W., 20 lks. dist. mkd. T28S R3W S6 BT.

Survey by John H. Markham, Jr. - For: J.G. Loewen Loggin Co. - Feb. 19, 1957 - C.S. File 42/246

Determined by O.B.T.s:
 26" dead Laurel, windfall bears N.40°E., 19.0 ft., found scribe O.B.T.
 At corner point, Set a 3/4" x 30" steel bolt 18" in ground, from which
 A 30" Cedar bears N.30°E., 31.0 ft. mkd. S32 BT.
 A 20" Laurel bears S.6°W., 31.0 ft. mkd. S6 BT.
 A 14" Laurel bears N.36°W., 42.0 ft. mkd. S31 BT.
 Closing cor. to secs. 5 & 6 bears East 11.2 ft.
 Main top bears West 110.0 ft.

BLM resurvey by Boyd W. Peterson, under Group #1480, Surveyed July 1989/May 1990 - (DCSO records Vol. 50 Page(s) 18829)

The standard cor. of secs. 31 and 32, perpetuated and recorded by John H. Markham Jr., Registered Engineer No. 2880, in 1957, from original evidence no longer in existence, monumented with an iron pipe, 1 in. diam., firmly set, projecting 9 ins. above ground, from which the remains of bearing trees mkd. by Markham:

- A burnt cedar stump, 20 ins. diam., bears N. 31 3/4° E., 46 lks. dist., no marks visible.
- A sawed madrone stump, 22 ins. diam., bears S. 9 3/4° W., 45½ lks. dist., no marks visible on burnt out center.

At the corner point
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

SC
 T 27 S R 3 W
S 31 | S 32
 1989

(Cont. Next Page)

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which new bearing trees
A fir, 6 ins. diam., bears N. 36¼° E., 22 lks. dist.,
mkd. T27S R3W S32 SC BT.
A fir, 5 ins. diam., bears N. 83° W., 33 lks. dist.,
mkd. X BT.
Deposit a white "DEEP-1" magnetic marker at the base and
reset the iron pipe alongside the stainless steel post.

Found OK by T. Baker, May 2001 - M138-15