

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5019)

Set cedar post, 3 ft. long, 3" sq., firmly in the ground for 1/4 sec. cor. mkd 1/4 S from which
A fir, 24" dia., bears S.72°W., 19 lks., mkd: 1/4 S BT.
A fir, 40" dia., bears N.60°E., 20 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Boyd Peterson, Cadastral Surveyor, under Group #1480, surveyed July 1989/May 1990 - (DCSO records Vol. 50 Page(s) 18836-7)

The 1/4 sec. cor. of secs. 31 & 32, perpetuated by Lecklider, in 1959, determined from the remains of the original BTs:
A sawed fir stump, 53" dia., bears N.60°E., 23 lks. no marks visible. (Record, 20 lks.)
A fir, 38" dia., bears S.72° ., 21 lks. with scribe marks 1/4 BT visible on bark blaze (Record, 19 lks.)
and a bearing tree mkd. by persons unknown
A cedar, 12" dia. bears N.25 1/4°E. 18 lks. with healed blaze
At the corner point
Set a stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd. T 27 S R 3 W
1/4
S 31 | S 32
1989

from which a new bearing tree
A fir, 23" dia., bears S. 17 1/4° E., 24 lks. mkd. 1/4 S32 BT.
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.