

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5021)

Set cedar post, 4 ft. long, 4" sq., firmly in the ground for cor. to secs. 19, 20, 29, & 30, T27S R3W S20 on NE, 19 on NW, S30 on SW., and S 29 on SE. faces, with 5 notches on E & 2 notches on S edges, from which

 A laurel, 12" dia., bears N.35°E., 20 lks., mkd: T27S R3W S20 BT.

 A fir, 10" dia. bears N.10°W. 74 lks. mkd: T27S R3W S19 BT

 A fir, 18" dia. bears S.85°W. 58 lks. mkd: T27S R3W S30 BT

 A fir, 24" dia. bears S.50°E., 7 lks. mkd: T27S R3W S29 BT

G. Robert Lecklider - For: Wilbur Lbr. Co., Evans Products & US Plywood - Aug. 1960 - M19-51

Found - 30" Fir S.50°E., 4.6 ft. rescribed
 36" Fir stump S.85°W., 38.5 ft.
 14" Fir N.10°W., down

Set - Steel tube with survey cap
 21" Fir N.62°E., 30.7 ft.
 9" Cedar N.27°W., 22.5 ft.

Douglas Co. Surveyors Office - L. E. Monrean - P L Earle - K Cheney - J H Cook - July 20, 1976 - C.S. File 59/18-7

Found - 5/8" Steel tube with alum cap mkd. "property corner"
 10" Fir now an 18" windfall bears N.10°W., 48.8 ft. No scribing found.
 18" Fir, now 38" stump bears S.85°W., 38.3 ft. No scribing found.
 24" Fir, now 27" bears S.50°E., 4.6 ft. Tree scribed per orig. "T 2 R S" legible, per 1960 Ren. "S 29 RF 4° 9 BT".
 21" Fir, now 22" stump beats N.62°E., 30.7 ft. stump scribed "FRL4 0/9 BT"
 9" Red Cedar now 11" bears N.27°W., 22.5 ft. scribe visible in partially healed blaze.

Set - BC at sec cor stamped: Douglas County Surveyors Office

T27S	R3W
S 19	S 20
S 30	S 29
1976	

Set steel tube beside cap.
New BTs- An Incense Cedar, 12" bears N.59°E., 18.5 ft. Tree blazed and scribed "T27S R3W S20 CS BT.

continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by A Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Survey Tech, under Group No. 2189 surveyed June/Sept 2008 - (DCSO records Vol. 57 Page 22491)

The cor. of secs. 19, 20, 29, and 30, perpetuated by Lecklider, in 1960, further perpetuated by the Douglas County Surveyor's Office in 1976, monumented with an iron post, 2" dia., firmly set, projecting 6" above the ground, (alongside of which is a steel tube, 1" dia., firmly set, projecting 1" in. above the ground), with brass cap (properly) mkd. from which the remains of the orig. bearing trees

A burnt fir snag, 30" dia., bears S.34¼°E., 4.6 ft., with scribe marks R3W S29 BT visible in the bark. (Record, S.50°E.)

A sawed fir stump, 22" dia., bears S.85°W., 36.3 ft., with no marks visible. (Record, 38.3 ft.) and the remains of a bearing tree mkd. by Lecklider

A cedar snag, 13" dia., bears N.32°W., 22.6 ft., with no marks visible on an open blaze. and new bearing trees

A fir, 6" dia. bears N.56°E., 3.1 ft. mkd. T27S R3W S20 BT

A fir, 5" dia. bears S.4½°E., 18.3 ft. mkd T27S R3W S29 BT

A fir, 5" dia., bears S.28°W., 28.4 ft., mkd. X BT.

A chinquapin, 5" dia., bears N.58°W., 23.3 ft., mkd. T27S R3W S19 BT.

The geographic position (NAD 1983 (CORS 96)) of the corner of sections 19, 20, 29, and 30, as determined in a least squares adjusted network of conventional survey control and GPS occupied points, utilizing dual frequency, carrier phase GPS receivers, relative to National Spatial Reference System (NSRS) Continuously Operating Reference Stations (CORS) "CAPE BLANCO CORS ARP" and "DOUGLAS COUNTY SURVEYORS OFFICE CORS ARP", is as follows:

Latitude: 43°11'56.16"N Longitude: 123°05'25.52"W

Fd OK by Ken Hoffine - July 2012 - M164-13