

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5024)

Set cedar post, 4 ft. long, 4" sq. firmly in the ground for cor. to secs. 17, 18, 19, & 20, mkd: T27S R3W S17 on NE, Sec. 18 on NW, S19 on SW & S20 on SE faces; with 5 notches on E & 3 on W edges, from which
A fir, 30" dia. bears N.30°E. 26 lks. mkd: T27S R3W S17 BT
A cedar, 12" dia., bears N.80°W., 26 lks., mkd: T27S R3W S18 BT.
A cedar, 24" dia., bears S.55°W., 55 lks., mkd: T27S R3W S19 BT.
A cedar, 24" dia., bears S.85°E., 24 lks., mkd: T27S R3W S20 BT.

G. Robert Lecklider - For: Wilbur Lbr. Co., Evans Products & US Plywood - Aug. 1960 - M19-51

This corner set from calls by prop. meas. from Creeks North, South, & East, shown as per GLO field notes.
Set - Steel tube with survey cap:
46" fir S.15°W., 41.0 ft.
22" cedar N.18°W., 52.9 ft.
12" cedar S.19°E., 89.7 ft.
5" hem. N.25°E., 34.7 ft.

BLM dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Garry L. Moore, Surveying Technician, under Group #1416, surveyed Oct. 1987 - March 1988 - (DCSO records Vol. 48 Page(s) 18592-3)

The cor. of secs. 17, 18, 19 & 20, reestablished & recorded by Lecklider, in 1960, from topography calls to creeks, N., S., And E., and is accepted as the best available evidence of the orig. corner positions; monumented with an iron rod, 1/2" dia., firmly set, projecting 12" above ground, with an aluminum cap, 1" dia., mkd. PROPERTY CORNER, from which the remains of the bearing trees mkd. by Lecklider:
A hemlock, 8" dia., bears N.21½°E., 52 lks. with partially healed burned blaze.
A root hole, bears S.5°W., 64 lks., with a burned down fir alongside, 46" dia., no marks visible.
A burned cedar snag, 25" dia., bears N.21°W., 80 lks., no marks visible.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, directly over the iron rod, with brass cap mkd.
continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T27S R3W
S 18|S 17
S 19|S 20
1987

from which a new bearing tree

A burned hemlock snag, 8" dia., bears S.3½°W., 16 lks.,
mkd. T27S R3W S19 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless
steel post.

The Corner is located in the Fall Creek Fire area.

From this point, the United States Coast and Geodetic Survey
triangulation station "LANE 1953" bears S.47°58'31"W.,
147.514 chs., monumented with a brass tablet, 3½" dia. , set
in a concrete post, 7x7" square, projecting 7" above ground,
with top mkd. LANE 1953 and a triangle.