

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs 7, 8, 17, & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5026)

Set Laurel post, 4 ft. long, 4" sq., firmly in the ground for cor. to secs. 7, 8, 17 and 18, mkd. T27S R3W S8 on NE, S7 on NW, S18 on SW., and S17 on SE. faces, with 5 notches on E and 4 on S edges, from which
 A laurel, 12" dia., bears N.78°E., 54 lks., mkd: T27S R3W S8 BT.
 A cedar, 10" dia. bears N.63°W. 8 lks. mkd: T27S R3W S7 BT
 A fir, 12" dia. bears S.17°W. 15 lks. mkd: T27S R3W S18 BT
 A fir, 16" dia. bears S.28°E., 8 lks. mkd: T27S R3W S17 BT

Douglas Co. Surveyors Office - A. Boyer, Co. Surveyor - Wit. Otto Rowe & Bert Delzine - June 12, 1942 - C.S. File 36/32

Set a new BT in sec. 8 because the orig. BT a Laurel N.78°E., 54 lks., is gone. Marked a new BT as follows:
 A laurel, 36" dia., bears N.80°E., 97 lks., mkd: S8 T27S R3W CSBT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S. Bilow - Oct. 14, 1957 - C.S. File 49/14-6

Found - The four BTs as Boyer recorded in 1943, except the orig. 10" now 30" Cedar I find should be N.63°W., 9.2 ft. record N.63°W., 5.3 ft.
Set brass cap at corner mkd: County Surveyors Office 1957
 S 7 | S 8
 S 18 | S 17
I do not scribe or rescribe new BTs.

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12436)

The cor. of secs. 7, 8, 17, & 18, perpetuated and recorded by Byron, in 1957, at record bearing and distance from two orig. BTs and record bearing from a third orig. BT, monumented with an iron pipe, 1" dia., firmly set in a mound of stone, 3 ft. base, to top, with brass cap (properly) mkd. from which original bearing trees:
 A fir, 25" dia., bears S.28°E., 8 lks. bark scribed S17 BT
 A fir, 17" dia., bears S.17°W., 15 lks., bark scribed S18 T27S R3W BT.
 A cedar, 28" dia., bears N.63°W., 12 lks., bark scribed S7 T27S R3W BT. (Record distance 8 lks.)
continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and County Surveyor's bearing tree:
A madrone, 36" dia., bears N.80°E., 97 lks., bark scribed
S8 T27 R3W.

At the corner point
Set an iron post, 28" long, 2½" dia., on an X marked on
bedrock, and in a mound of stone, 3½ ft. base, to top, with
brass cap mkd.

T27S R3W
S 7 | S 8
S 18 | S 17
1958

from which

A chinquapin, 6" dia., bears N.29°E., 32 lks., mkd. T27S
R3W S8 BT.

A fir, 23" dia., bears S.71½°E., 62 lks. mkd. T27S R3W
S17 BT.

A fir, 16" dia. bears S.59°W. 38 lks. mkd. T27S R3W S18 BT

A fir, 35" dia. bears N.76¾°W. 30 lks. mkd. T27S R3W S7 BT

Deposit county surveyor's iron pipe alongside iron post.

Glenn S. Baughman - For: Teeco - Sept. 1978 - M73-56 & M74-29

Set - Brass cap

BTs - 24" D. Fir bears S.5°E., 12.5 ft scribed T27S R3W S17 BT

40" Cedar bears N.67°30'E., 131.0 ft. scribed T27S R3W
S8 BT.

12" Cedar S.81°15'W., 94.3 ft. scribed T27S R3W S18 BT.

No trees in section 7.

Douglas Co. Surveyors Office - Randall Smith - Stephen
Flause - Sept. 8, 1988 - C.S. File 62/55-5

Found - A 1958 BLM ¾" brass cap on a 2½" O.D. iron pipe
firmly set flush in rocks.

A 2½" dia. brass cap on a 1½" O.D. iron pipe
protruding 16" above a 2 ft. dia. mound of stone.
This BC/IP bears S.77½°W., 20.5 ft. from 1958 BLM
BC/IP.

(All original BTs gone. BT from 1942 ren. gone.
NE and NW BTs from 1958 BLM resurvey are gone.)

23" now 40" dia. D. Fir with a fully healed single
blaze bears S.66°E., 40.9 ft. (Rec. S.71½°E.,
40.9 ft.) 1958 BLM BT.

16" now 17" dia. 35 ft. high D. Fir snag with a
previously opened low blaze, scribe marks visible
"27" bears S.54½°W., 22.7 ft. (rec. S.59°W., 25.1
ft. dist. is to center of trunk.) 1958 BLM BT

continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17, & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A recently marked 3" "X" in a high rock outcrop, bears N.42½°W., 60.1 ft. (Rec. from 1987 BLM tag found on rock outcrop N.40¾°W., 60.1 ft.) Southeast BT found alive with a partially healed burnt over blaze, faint scribe marks visible, we axed out scribing and remove Baughman's BT tag. Northeast BT found down and burnt. No scribing visible in open blaze, Baughman's BT tag removed. Southwest BT found down with a partially healed single blaze, scribing visible, We axed out scribing and remove Baughman's BT tag.

Set - Marks on Baughman's 1978 brass cap are stamped out, with the exception of "1978 OLS 536".

New BTs- 24" dia. D.Fir (formerly Baughman's SE BT" single blazed 6 ft. above ground "T27S R3W S18 CS BT" bears S.47°W., 24.4 ft.

3" dia. madrone bark scribed "X BT" bears N.87½°E., 20.3 ft.

Note: Corner lies at south edge of an excavated rock ridge, in a rock slide. A possible magnetic attraction in area of corner, large amount of rock around corner.

BLM dependent resurvey by Wayne L. Rogers, Cadastral Surveyor & Garry L. Moore, Surveying Technician, under Group #1416, surveyed Oct. 1987 - March 1988 - (DCSO records Vol. 48 Page(s) 18596-7)

The cor. of secs. 7, 8, 17, & 18 (the monument reestablished in 1958 was found out of position under a rock slide), determined a record distance from the remains of the BTs mkd. by Corbin:

A fir snag, 20" dia., bears S.65°E., 62 lks., with healed blaze. (Record S.71½°E.)

A fir snag, 20" dia., bears S.56¾°W., 38 lks. with scribe mark 2 visible on opened blaze. (Record S.59°W.)

At the corner point
Reset the iron post, 28" long, 2½" dia., 14", in the ground, in a mound of stone, 4 ft. base, to top, with brass cap (properly) mkd.
from which a bearing object
A basalt rock outcrop, 10 ft. x 10 ft. x 25" high, bears N.40¾°W., 91 lks., mkd. X on top.

From this point, a point established by Baughman in 1978, bears S.77°25'30"W. 0.306 chs., monumented with an iron post, 1½" dia., firmly set, projecting 15" above ground, with brass cap mkd. T27S R3W S7 S8 S17 S18 1978 RLS 536.

continued next page

3

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17, & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Retracement & rehabilitation by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2300 surveyed March 2008 - (DCSO records 2009 BLM Plat & Vol. 56 Page 21840)

The cor. of secs. 7, 8, 17, & 18 perpetuated by the Douglas Co. Surveyors Office in 1988, monumented with an iron post 2½" dia., firmly set, projecting 14" above the ground, in a mound of stone, 3½ ft. base to top, with brass cap (properly) mkd. from which the remains of BTs mkd by Corbin

A fir, 52" dia. bears S.65°E., 40.9 ft with a healed blaze

A fir, 34" dia., bears S.49¼°W., 25.1 ft. with no marks visible on an open blaze. (Rec. S.56¼°W.)

and a bearing object mkd. by Rogers & Moore

A rock outcrop, 10 ft. x 10 ft. 16" high, bears N.40¾°W., 60.1 ft. mkd X on top.

and a new BT

A madrone, 5" dia., bears N.23¼°E., 34.7 ft., mkd: X BT. Corner is located in rock debris pushed out of rock quarry. From this point, a point established by Baughman in 1978, bears S.78°24'01"W., 20.3 ft. (rec. S.77°25'30"W., 20.20 ft.) monumented with an iron post, 1" dia., firmly set, projecting 21" above the ground, with brass cap mkd. 1978 OLS 536. The remainder of the cap markings reported by Rogers & Moore were obliterated & the BTs mkd by Baughman were defaced by the Douglas Co. Surveyors Office in 1988.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

The geodetic position shown hereon was determined by a tie utilizing dual frequency carrier phase GPS receivers relative to the National Spatial Reference System. (NAD 1983 (CORS96))

Latitude: 43°13'40.64"N Longitude: 123°05'23.62"W