

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by A.R. Flint & L.L. Williams, Under Contract #151, dated May 23, 1871 (DCSO records Vol. 12 Page(s) 4972)

-----

Set post to cor. of secs. 5, 6, 7, & 8, from which

- A B.Oak, 10" dia., bears S.45°W., 38 lks.
- A Laurel, 4" dia., bears N.70°W., 30 lks.
- A W.Oak, 4" dia., bears S.50°E., 94 lks.
- A Laurel, 6" dia., bears N.2°E., 12 lks.

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5028)

-----

Cor. to secs. 5, 6, 7, & 8, which is a post, 4" sq., mkd. T27S R3W S5 on NE, S6 on NW, S7 on SW and S8 on SE faces, from which

- A W.Oak, 6" dia. bears N.20°E. 12 lks. mkd: T27S R3W S5 BT
- A Laurel, 4" dia., bears N.70°W., 30 lks., mkd: T27S R3W S6 BT.
- A B.Oak, 10" dia., bears S.45°W., 38 lks., mkd: T27S R3W S7 BT.
- A W.Oak, 4" dia. bears S.50°E. 94 lks. mkd: T27S R3W S8 BT

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12438-9)

-----

Point for the cor. of secs. 5, 6, 7, & 8 proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 25" in the ground, with brass cap marked:

T27S	R3W
<u>S 6</u>	<u>S 5</u>
S 7	S 8
1958	

from which

- A madrone, 6" dia., bears N.47½°E., 22 lks., mkd: T27S R3W S5 BT.
- A madrone, 6" dia., bears S.30°E., 24 lks., mkd: T27S R3W S8 BT.
- A madrone, 6" dia., bears S.66°W., 13 lks., mkd: T27S R3W S7 BT.
- A madrone, 6" dia., bears N.36°W., 63 lks., mkd: T27S R3W S6 BT.

continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

David Edwards - For: Roseburg Resources - May 2001 - M138-18  
& C.S. File 65/34-8

-----

Found - BLM brass cap  
10" dia., Madrone bears N.47½°E., 14.52 ft.  
9" dia., Madrone bears S.66°W., 8.58 ft.  
9" dia., Madrone bears N.36°W., 41.58 ft.  
New BT - 8" dia., Madrone bears S.40°E., 14.40 ft.

Fd. Ok by D. Edwards, 11/2006 - M151-61  
Fd. Ok by K. DeGroot, 8/2005 - M146-27