

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by A.R. Flint & L.L. Williams, Under Contract #151, dated May 23, 1871 (DCSO records Vol. 12 Page(s) 4972)  
-----

Set post for 1/4 sec. cor. from which  
A B.Oak, 10" dia., bears East, 4 lks.  
A fir, 4" dia., bears N.30°W., 5 lks.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy -  
Witnesses: Ed Russell & W.E. Chapman - Dec. 26, 1922 - Vol. 3 Pg 139A  
-----

Identified location from orig. BTs  
Set a fir post for corner from which a  
Fir 10" dia., bears S.25°E., 10.5 ft.  
Fir 14" dia., bears N.30°W., 3.3 ft. OBT

David Edwards - For: Roseburg Resources - May 2001 - M138-18 & C.S. File 65/34-8  
-----

A diligent search was made for Orig. & 1922 D.C.S. Ren. evidence at the 1/4 corner to sections 5 & 6 with negative results. The corner was set by proportionate method.  
Set - 5/8"x44" steel rod w/alum cap stamped "ROSEBURG RESOURCES COMPANY" and "LS 2339"  
A 14" dia., Fir bears N.30°E., 25.70 ft.  
A 9" dia., Fir bears N.76°E., 25.02 ft.  
A 15" dia., Fir bears S.1°E., 20.30 ft.  
A 9" dia., Fir bears S.74°W., 2.48 ft.  
BTs are scribed according to the 1972 BLM Manual and are measured to the center of tree at root crown.

Fd. ok by K. DeGroot, 8/2005 - M146-27