

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. 5 & 6; 31 & 32 of T 26-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 10 Page 4350)

Set post, cor. to secs. 31, 32, 5 and 6, from which
A W.Oak 8" dia., bears N.23°W., 55 lks. dist.
A B.Oak 15" dia., bears N.18°E., 79 lks. dist.
A B.Oak 18" dia., bears S.60°E., 22 lks. dist.
A B.Oak 5" dia., bears S.61°W., 104 lks. dist.

A.R. Evans - R.G. Irving - Oct. 19, 1950 - C.S. File 44/61

Found BT alive and standing, 8" W.Oak now 15" N.23°W., 55 lks.
Set - $\frac{3}{4}$ " Iron rod for corner.
Blazed and scribed new BTs:
20" Fir S.32°W., 30.9 ft. mkd. T27S R3W S6 CS BT.
30" B.Oak N.45°W., 65.0 ft. mkd. T26S R3W S31.
No other trees available.

BLM survey, Harold D. Corbin - Under special instructions
dated May 3, 1957, Survey Aug/Nov 1958 (DCSO records, Vol.
29 Page 12440)

Found point for cor. perpetuated with an iron post, $\frac{3}{4}$ " dia.,
firmly set, 1" above ground at record bearing and distance
from the only remaining original bearing tree:

A W.Oak stump 15" dia., bears N.23°W., 55 lks. dist.,
with illegible scribe marks on a partially healed
blaze.

and locally established bearing trees:

A Fir stump 20" dia., bears S.32°W., 47 lks. dist.

A W.Oak stump 30" dia., bears N.45°W., 98½ lks. dist.,
with scribe marks R3W S31 CS BT visible on an
opened blaze.

At the corner point, set an iron post 28" long 2½" dia., 27"
in the ground, with brass cap mkd.

T 26 S R 3 W

S 31 | S 32

S 6 | S 5

T 27 S

1958

A Fir 26" dia., bears N.61¾°E., 1202 lks. dist. mkd.
T26S R3W S32 BT.

(Cont. Next Page)

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. 5 & 6; 31 & 32 of T 26-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 11" dia., bears S.11¼°E., 128 lks. dist., mkd.
T27S R3W S5 BT.
A Fir 6" dia., bears S.28°W., 230 lks. dist., mkd.
T27S R3W S6 BT.
A Fir 6" dia., bears N.52¼°W., 170 lks. dist., mkd.
T26S R3W S31 BT.
Deposit local corner material alongside iron post.

Fd. OK, Doug. County Surveyors Office - 1957 - C.S. 49/14-10
Found OK by D. Edwards, May 2001 - M138-18 and CS 65/34-8

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause -
2/14/2008 - C.S. File 67/25-14

Found - 3¼" dia., (BLM) brass cap markings becoming
indistinct, is fd 3" below ground.
11" now 32" dia., x 3 ft. tall D.Fir stump (cut on
angle) healed low blaze visible bears S.11¼°E.,
84.5 ft. (agrees w/rec) 1958 BT
6" now 36" dia., x 1 ft. tall D.Fir stump, healed
low blaze visible bears S.28°W., 150.6 ft.
(Rec. S.28°W., 151.8 ft. 1958 BT.
6" now 14" dia., x 6" tall rotten D.Fir stump, part
of lower healed blaze visible bears N.52¼°W.,
112.2 ft. (agrees w/rec) 1958 BT.
26" now 43" dia., D.Fir fully healed single blaze
visible bears N.61¼°E., 793.3 ft. - checked by
traverse, no longer direct line of sight -
(agrees w/rec) 1958 BT

New - 14" dia., I.Cedar, double blazed & scribed "T27S R3W
S6 CS BT" bears S.21½°W., 39.3 ft.
Double trunk madrone, northerly trunk is 18" dia.,
and is scribed "T26S R3W S31 CS BT" center of
root crown bears N.62°W., 16.4 ft.
N.45°W., 7 ft. to old fence corner with decapitated
fences running West & North.

Note - Corner lies 8 ft. east from center of graveled rd.
older clearcut to NW. New clearcut in all other
quadrants with isolated timber patches near
ridge top.
Compass decl. 16¼°E.