

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5020)

Set laurel post, 3 ft. long, 3" sq., firmly in the ground for 1/4 sec. cor. mkd 1/4 S on N & S faces, from which
A fir, 36" dia., bears N.10°E., 57 lks., mkd: 1/4 S BT.
A fir, 16" dia., bears S.80°W., 87 lks., mkd: 1/4 S BT.

G. Robert Lecklider - For: Wilbur Lumber Co. - Nov. 1959, filed Dec. 8, 1959 - M 16-57

Found - 48" fir N.10°E., 37.6 ft. (Faint bark scribe)
34" Fir S.80°W., 57.4 ft. (Faint bark scribe)
Set - rescribed Orig. trees.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - June 20, 1969 - C.S. File 54/40-177

Found - OBTs as follows - (See also 1959 ren.)
Orig. 36" Now 50" Fir N.10°E., 37.6 Ft. Alive -
Orig. bark scribe & Shrums bark scribe.
Orig. 16" now 36" Fir S.88°W. (Record S.80°W.) 57.4
Ft. Alive- Orig. bark scribe only. Fragmentary -
Shrums bark scribe o.k. at cor. point.
Set - 1" I.P. & Brass Cap Mkd: County Surveyors T 27 S
Office, 1969 1/4 S 29 R3W
S 32
New BTs- 13" D.Fir N.63°W., 12.6 Ft. Mkd. 1/4 S32 CS BT
This Cor. lies on E. W. cutting line- clear cut in Sec. 32