TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5027)

Set cedar post, 3 ft. long, 3" sq., firmly in the ground for ¼ sec. cor. mkd ¼ S on S & N faces, from which
A laurel, 24" dia., bears S.45°E., 20 lks., mkd: ¼ S BT.
A laurel, 24" dia., bears N.70°W., 20 lks., mkd: ¼ S BT.

Douglas Co Surveyors Office - A Boyer, Co Surveyor - Wit Otto Rowe & Orville Anderson - June 13, 1942 - C.S. File 36/32

Renewal from Orig. BT in SE quadrant (Sec. 17) Set 4x4 post for corner & marked new trees as follows:
Madrone 24" dia. bears N.70°W., 34.0 ft. marked ¼ S8 CS BT

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12443-4)

The ¼ sec. cor. of secs. 8 & 17, perpetuated with a cedar post, 3x3" cross section, firmly set, 2½ ft. above ground, with scribe marks S8 on the NE & S17 on the SW faces, at record bearing & dist. from the only remaining orig. BT:
A madrone, 28" dia., bears S.45°E., 20 lks, with scribe marks ¼ S17 BT visible on an opened blaze.
and locally established BT
A madrone, 22" dia., bears N.70°W., 52 lks., with scribe marks ¼ S8 CS BT visible on opened blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap marked: T27S R3W
¼ S 8 / S 17
1958
from which
A cedar, 12" dia., bears N.36½°W., 57 lks., mkd: ¼ S8 BT.
A chinquapin, 11" dia. bears S.31°E. 53 lks. mkd: ¼ S17 BT
Deposit local corner material alongside iron post.

David Edwards - For: Seneca Jones Tmbr Co - 3/2010 - M 160-42

Found - Brass cap
All old BTs gone.
New - 5" Fir bears N.87°W., 8.7' scribed
5" Fir bears N.79°E., 28.7' "¼ S8 BT"
6" Fir bears S.33½°E., 18.0' scribed "¼ S17 BT"
Set 6' steel post 2' north.