

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by A.R. Flint & L.L. Williams, Under Contract #151, dated May 23, 1871 (DCSO records Vol. 12 Page(s) 4972)

Set post to ¼ sec. cor, from which
A fir, 4" dia., bears N.20°E., 4 lks.
A fir, 4" dia., bears S.20°W., 4 lks.

Douglas Co. Surveyors Office - B.B. Irving, DCS - Wit: N.E. Richardson, N.G. Williams, & Bert Delzine - Aug. 12, 1939 - C.S. File 47/66

Location identified from both orig. BTs, one of which was chopped out & showed scribed marks in excellent shape. The trees are a Fir 18" dia., S.20°W., 4 lks., & a fir 18" dia., N.20°E. Drove an iron pipe 1/2" x 24" long 20" in the ground for the corner from which
A Fir 20" dia., bears N.65°W., 57 lks.
A fir 18" dia., bears S.20°W., 4 lks. (Orig. BT)

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12439)

The ¼ sec. cor. of secs. 5 & 8 perpetuated with an iron pipe, 1/2" dia., firmly set, 2" above ground at record bearing & distance from the two orig. BTs
A fir, 25" dia., bears N.20°E., 4 lks., with an open blaze, no marks visible.
A fir, 25" dia., bears S.20°W., 4 lks., bark scribed ¼ S5 BT CS.

At the corner point
Set an iron post, 28 long, 2½" dia., 26" in the ground, with brass cap marked:
T27S R3W
¼ S 5
 S 8
 1958

from which
A cedar, 9" dia., bears N.51¼°W., 54 lks., mkd: ¼ S5 BT.
A fir, 8" dia., bears S.61°E., 32 lks., mkd: ¼ S8 BT.
Deposit local corner material alongside iron post.

Fd. Ok by D. Edwards, 5/2001 - M138-18 & C.S. File 65/34-8
Fd. BC & 4 BTs (now high stumps - No trees within 200') by D. Edwards, 3/2010 - M160-42