

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>Original - Addison R. Flint, Contract #56 dated March, 1855 (DCSO Records, Volume 10 Page 4350)</p> <p>-----</p> <p>Set 1/4 sec. post, from which A B.Oak 7" dia., bears N.49°W., 37 lks. dist. A W.Oak 7" dia., bears S.27°E., 89 lks. dist.</p>
<p>Ben B. Irving; A.R. Evans. N.E. Richardson - 10/1950 -CS 44/61</p> <p>-----</p> <p>Set by proportionate measurement. Set 1" I.P. with brass cap marked County Surveyors Office, T26S R3W 1/4 S32 T27S R3W 1/4 S5. Blazed and scribed 2 BTs: 8" W.Oak N.60°W., 19.1 ft. 8" W.Oak S.53°E., 53.6 ft.</p>
<p>Douglas Co. Surveyors Office - V.R. Tracy - 2/1966 - C.S. 54/7</p> <p>-----</p> <p>Searched for, not found. Corner falls in cat cleared field.</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 5/15/2001 - C.S. File 66/21-18</p> <p>-----</p> <p>Found - 1950 DCSO bent BC/IP protrudes 3" above ground bent 5" NW of plumb position referenced BC/IP removed and straightened flanges in good shape IP measures 36" long, mkd: COUNTY SURVEYOR COR 1/4 T 26 R 3 <u>S 32</u> S 5 T 27 R 3 OFFICE</p> <p>No BTs found, possible root hole of 1950 NW BT (Rec. N.60°W., 19.1 ft.)</p> <p>Set - Brass cap iron pipe returned to plumb position, protrudes 3" above ground. 13" dia., D.Fir double blazed & scribed "1/4 S5 CS BT" bears S.21°E., 33.7 ft. 6" dia., D.Fir double blazed & scribed "1/4 S5 CS BT" bears S.5°W., 42,3 ft. 7" dia., D.Fir double blazed & scribed "1/4 S32 CS BT" bears N.13°E., 67.9 ft. 7" dia., W.Oak double blazed & scribed "1/4 S32 CS BT" bears N.29°W., 64.0 ft. (Compass decl. 17 3/4°E)</p>
<p>continued next page</p>

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 5; & 32 of T26-3

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Fd. BC & 4 BTs by K. Hoffine, 7/2007 - M153-77