

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec Cor for 32 & 33 only, (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by S.C. Flint, Under Contract #454, dated June 19, 1882 (DCSO records Vol. 12 Pg 4976)

Set a Laurel post 4 ft. long, 4" sq., firmly in the ground for standard cor. to secs. 32 and 33, mkd. S C T27S R3W on N., S33 on E., and S32 on W. faces with 4 notches on E. and 2 notches on W. faces, from which

A Fir 16" dia., bears N.16°E., 46 lks. dist. mkd. T27S R3W S33 BT.

A Laurel 30" dia., bears N.25°W., 49 lks. dist. mkd. T27S R3W S32 BT.

A Fir 14" dia., bears S.30°W., 31 lks. dist. T28S R3W S5 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell & Wm. Stoffel - Aug. 1962 - C.S. File 52/126-31

Found - Orig. 16" now 24" R.Fir N.16°E., 30.4 ft., shows good scribing.

Orig. 30" now 36" Fir, not Laurel, N.25°W., 32.3 ft., shows good bark scribing.

Orig. 14" now 24" Fir S.30°W., 20.5 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

T 27 S R 3 W

S 32 | S 33

T28S

1962