TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5013)

Set Cedar post, 4 ft. long, 4" sq., firmly in the ground for cor. to secs. 20, 21, 28 and 29, mkd. T27S R3W S21 on NE., S20 on NW., S29 on SW., and S28 on SE. faces, from which
A hemlock, 8" dia., bears N.81°E., 44 lks., mkd: T27S R3W S21 BT.
A laurel, 5" dia., bears N.35°W., 53 lks., mkd: T27S R3W S20 BT.
A fir, 6" dia. bears S.75°W., 57 lks. mkd: T27S R3W S29 BT
A fir, 12" dia. bears S.53°E. 34 lks. mkd: T27S R3W S28 BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S. Bilow - Oct. 15 1957 - C.S. File 49/14-8

Found - Orig 12" now 30" It. Fir S.53°E. 22.4 ft. Old bark scribe "BT". Shows old face above. I do not open.
All other BTs. gone. I also find old rotted stake at corner, maybe Original.
Set Brass Cap at cor mkd County Surveyors Office S20|S21 T27S
1957 S29|S28 R3W
New BTs- 5" Hemlock bears N.66°W., 5.4 ft. scribed S20 CS BT.
8" R.Fir bears S.45°W., 11.2 ft. scribed S29 T27S R3W CS BT.
10" Hemlock bears N.20½°E. 18.2 ft. scribed S21 T27S R3W CS BT.

Gerald Nygren - For: Seneca Jones Timber Co - 10/2018 - M174-80

Found - 1957 Co. Surveyor brass cap per rec.
(1882) 12" Fir, now 39" bears S.53°E., 22.4' healed blaze
(1957) 8" R.Fir, now 8" snag bears S.45°W., 11.2' no visible scribe
10" Hemlock, now 17" bears N.20°30'E., 18.2' healed blaze
New BTs- 8" D.Fir bears N.69°W., 27.4' scribed: "T27S R3W S20 BT"
6" D.Fir bears S.43°W., 17.2' scribed: "X BT"