

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5016)

Set Cedar post, 4 ft. long, 4" sq., firmly in the ground for cor. to secs. 8, 9, 16 & 17, mkd. T27S R3W SW 9 on NE, S8 on NW S17 on SW & S 16 on SE faces, with 4 notches on E and S edges, from which

- A laurel, 16" dia., bears N.50°E., 46 lks., mkd: T27S R3W S9 BT.
- A fir, 40" dia. bears N.42°W., 55 lks. mkd: T27S R3W S8 BT
- A fir, 36" dia. bears S.4°W., 20 lks. mkd: T27S R3W S17 BT
- A fir, 30" dia. bears S.88°E. 74 lks. mkd: T27S R3W S16 BT

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12434)

The cor. of secs. 8, 9, 16, and 17, perpetuated with a cedar stake, 2x2" cross section, firmly set, 4 ft. above ground, at record dist. from the four original BTs:

- A madrone, 24" dia. , bears N.50°E., 46 lks., with a healed blaze.
- A fir, 53" dia., bears S.83°E., 74 lks., with an old axe mark visible.. (Record bearing S.88°E.)
- A fir, 45" dia., bears S.4°W., 20 lks. bark scribed S17 BT
- A fir, 53" dia., bears N.42°W., 55 lks., with bark scribe S and axe marks visible.

At the corner point

Set an iron post, 28 long, 2½" dia., 26" in the ground, with brass cap marked:

T27S	R3W
S 8	S 9
S 17	S 16
1958	

from which

- A cedar, 10" dia., bears N.14°E., 47 lks., mkd: T27S R3W S9 BT.
- A madrone, 8" dia., bears S.31¼°E., 44 lks., mkd: T27S R3W S16 BT.
- A cedar, 9" dia., bears S.48°W., 80 lks., mkd: T27S R3W S17 BT.
- A chinquapin, 10" dia., bears N.73½°W., 94 lks., mkd: T27S R3W S8 BT.

Deposit local corner material alongside iron post.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - April 5, 1989 - C.S. File 62/63-9

Found - A 1958 3½" dia. BLM disk marked correctly, on a 2½" O.D. galv. I.P. firmly set and protruding 5" above ground.

Evidence of four original bearing trees found:

A laurel, 16" now a 22" DBH madrone with fully healed double blaze bears N.47°E., 31.2 ft. (Rec. N.50°E., 30.4 ft. good to center of tree at blaze height)

A 30" fir, now a 48" dia. 4 ft. high fir stump with no scribing or blazes visible bears S.80°E., 49.7 ft. (Orig. Rec. S.88°E., 48.8 BLM rec. S.83°E., 48.8 ft. dist. is possible face meas.)

A 36" fir now a 41" DBH D.Fir with burned bark scribing "S" visible bears S.04°W., 14.5 ft. (orig. rec. S.4°W., 13.2 ft. dist. this is a possible face measurement)

A fir 40" now a 48" dia. 3 ft. high fir stump with no blazes or scribing visible bears N.42°W., 37.6 ft. (Orig rec N.42°W., 36.3 ft this is a possible face measurement)

Evidence of 3 BTs from 1958 BLM dependent resurvey fd:

(The NE cedar bearing tree is not found due to road work in area)

An 8" madrone now a dead 7" DBH madrone snag with a healed single blaze bears S.29½°E., 28.6 ft. dist. (Rec. S.31¼°E., 29.0 ft. this a possible slope face measurement)

A 9" cedar now a dead 10" DBH cedar with a partially healed single blaze showing the scribing "27S R3W S17 B" bears S.48°W., 52.8 ft dist as per record.

A 10" chinquapin now a 10" DBH 8 ft. tall snag with a partially healed single blaze bears N.73½°W., 60.8 ft. dist. (Rec. N.73½°W. 62.0 ft. is a slope measurement)

New BTs- A 10" DBH madrone scribed "T27S R3W S17 CS BT" on a double blaze bears S.68½°W., 13.2 ft. dist.

An 8" DBH incense cedar scribed "T27S R3W S8 CS BT" bears N.66½°W., 28.0 ft. distant.

Monuments lies approx. ten feet southerly from centerline of a cat fire road near the top of a steep ENE slope at the west cutting line of a large clear cut. Clear cut extends up ENE slope from Jim Creek.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Boyd Peterson, Cadastral Surveyor, under Group #1480, surveyed July 1989/May 1990 - (DCSO records Vol. 50 Page(s) 18833-4)

The cor. of secs. 8, 9, 16 & 17 perpetuated & recorded by Smith in 1989, monumented with an iron post, 2½" dia., firmly set projecting 4" above ground, with brass cap (properly) mkd from which the remains of the original bearing trees

A madrone, 23" dia., bears N. 47° E., 46 lks. with healed blaze. (Record, N.50°E.)

A sawed fir stump, 48" dia., bears S.83°E., 74 lks., no marks visible.

A fir, 43" dia., bears S. 4° W., 20 lks., with scribe mark S visible on bark blaze.

A sawed fir stump, 48" dia., bears N.42°W., 55 lks., no marks visible.

and the remains of bearing trees mkd. by Corbin

A dead madrone, 7" dia., bears S.31¼°E., 44 lks., no marks visible on partially healed blaze.

A dead cedar, 9" dia., bears S. 48° W., 80 lks., with fragmentary scribe marks visible on partially healed blaze.

A chinquapin stump, 11" dia., bears N.73½°W., 91 lks., no marks visible on partially healed blaze (Rec 94 lks.)

and bearing trees mkd. by Smith

A madrone, 10" dia., bears S.66¼°W., 19½ lks., with scribe marks T27S R3W S17 CS BT on open, double blaze.

A cedar, 8" dia., bears N.67¾°W., 42 lks. with scribe marks T27S R3W S8 CS BT on open, double blaze.

and a new bearing tree

A fir, 6" dia., bears S. 24° E., 71 lks. mkd X BT.

From this point, the BLM Geodetic Control Station EC41005, at latitude 43°13'58.743"N., longitude 123°04'05.425"W. (NAD 1927), determined by the NAVSTAR GPS, bears N.6°39'29"E., 31.550 chs., monumented with an aluminum cap, 3" dia., set in concrete flush with the ground, mkd. EC41005 GPS 1989.

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2300 surveyed March/April 2008 - (DCSO records Vol. 56 Pg 21834)

The cor. of secs. 8, 9, 16, and 17, remonumented by Corbin in 1958, perpetuated by the Douglas County Surveyors Office in 1989, monumented with an iron post, 2½" dia., firmly set, projecting 4" above the ground, with brass cap (properly) mkd from which the remains of the original bearing trees

A fir, 42" dia., bears S.4°W., 13.2 ft with a healed blaze continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. Secs. 8, 9, 16, & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed fir stump, 49" dia., bears N.42°W., 36.3 ft., with no scribe marks visible on a partially healed blaze. and bearing trees mkd. by the Douglas County Surveyors Office

A madrone, 12" dia. bears S.64°W. 12.8 ft with fragmentary scribe marks visible on a partially healed blaze.

A cedar, 10" dia bears N.67¾°W. 27.6 ft with a healed blaze (See plat for bearings & distances of the lines)

The geographic position (NAD 1983 (CORS 96)) of the corner of sections 8, 9, 16, and 17, as determined in a least squares adjusted network of conventional survey control and GPS occupied points, utilizing dual frequency carrier phase GPS receivers, relative to National Spatial Reference System (NSRS) Continuously Operating Reference Station (CORS) "CAPE BLANCO CORS ARP" and National Cooperative CORS Network Station "ROSEBURG COOP CORS ARP", is as follows:
Latitude: 43°13'37.75"N. Longitude: 123°04'12.90"W.

Fd. ok by D. Edwards, 3/2010 - M160-42