

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5016-7)

Set cedar post, 3 ft. long, 3" sq., firmly in the ground for 1/4 sec. cor. mkd 1/4 S on E & W faces, from which
 A maple, 8" dia., bears N.89°W., 33 lks., mkd: 1/4 S BT.
 A fir, 6" dia., bears S.62°E., 59 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Boyd Peterson, Cadastral Surveyor, under Group #1480, surveyed July 1989/May 1990 - (DCSO records Vol. 50 Page(s) 18833-4)

The Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.
Set a stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd.
 T 27 S R 3 W
 1/4
 S 8 S 9
 1989
from which
 A fir, 11" dia., bears N.31 1/4°E., 58 1/2 lks. mkd. 1/4 S9 BT.
 A G.Fir, 5" dia., bears S.42 1/2°W., 12 1/2 lks. mkd. X BT.
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

Fd. ok by D. Edwards 11/2006 M151-61
Fd. as per M151-61 - by D. Edwards, 3/2010 - M160-42