

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 301100

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5 only, T28-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by William N. Gibb, Deputy Surveyor, under Contract #783, dated Dec. 3, 1908 - (DCSO records Vol. 13 Page(s) 5588-89)

-----  
Intersect Sixth Standard Parallel 65 lks. E. of cor. secs. 32 and 33, Set Fir stake 3 ft. long, 4" sq., 24" in the ground for closing cor. secs. 4 and 5, marked C C T28S R3W on S., S4 on E., and S5 on W. face, with 4 grooves on E. and 2 grooves on W. face, from which

A Laurel 12" dia., bears S.44°E., 37 lks. dist. mkd. T28S R3W S4 BT.

A Laurel 5" dia., bears S.37°W., 65 lks. dist. mkd. T28S R3W S5 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell & Wm. Stoffel, crew - Aug. 1962 - C.S. File 52/126-32

-----  
Found - Orig. 12" now 20" Laurel S.44°E., 24.4 ft., shows good scribing.

Orig. 5" now 10" Laurel S.37°W., 42.9 ft., old face rotted.

Set brass cap at cor. mkd. County Surveyors Office 1962  
T 27 S

-----  
S 5 | S 4  
T 28 S R 3 W

New BT - 13" Laurel bears S.10°W., 22.5 ft. scribed S5 T28S R3W CS BT.

Sec. Cor. for 32 & 33, T27S, bears N.76°W., 62.9 ft., not West 62.9 ft.