

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 33 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by S.C. Flint, under Contract #454, dated June 19, 1882 - (DCSO records Vol. 12 Page(s) 4976)

-----  
Set Cedar post 3 ft. long, 3" sq., for ¼ sec. cor., firmly in the ground mkd. S C ¼ S on N. face, from which  
A Chinquapin 8" dia., bears S.30°W., 10 lks. dist. mkd. S C ¼ S BT.  
A Fir 30" dia., bears N.55°E., 30 lks. dist. mkd. S C ¼ S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell & Wm. Stoffel - Aug. 1962 - C.S. File 52/126-31

-----  
Found - Orig. 30" now 72" Fir N.55°E., 19.8 ft., shows good old bark scribing.

We do not find orig. SW. BT.

Set Brass cap at cor. mkd: County Surveyors Office  
T 27 S R 3 W  
S ¼ S 33  
1962

New BT - 12" Laurel bears N.11°W., 32.7 ft. scribed ¼ S33 CS BT.