TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5013-4)

Set maple post, 3 ft. long, 3" sq., firmly in the ground for ¼ sec. cor. mkd ¼ S on N & S faces, from which
A laurel, 12" dia., bears N.21°E., 24 lks., mkd: ¼ S BT.
A fir, 20" dia., bears S.45°E., 30 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S. Bilow - Oct. 1957 - C.S. File 49/14-7

Found - The orig. 20" now 36" R.Fir BT. Good bark scribing "¼S BT"
The orig. NE BT not found.
Set brass cap at corner mkd: ¼ S 21 / S 28 T27S R3W County Surveyors Office 1957
New BTs- 7" Cedar bears N.7°W., 18.2 ft. scribed ¼ S21 CS BT.
16" R.Fir bears S.9°W., 27.7 ft scribed ¼ S28 CS BT.

Gerald Nygren - For: Seneca Jones Timber Co - 10/2018 - M174-80

Found - 1957 County surveyor brass cap per record
(1882) 20" Fir, now rotten stump bears S.45E., 19.8'
(1957) 16" R.Fir, now 32" bears S.09°W., 27.7'
visible scribe
New BTs- 7" Hemlock bears S.58°E., 26.9' scribed: "¼ S28 BT"
11" Cedar bears N.44°E., 16.2' scribed: "¼ S21 BT"
7" D.Fir bears N.02°E., 37.4' scribed: "¼ S21 BT"