

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5014)

Set Cedar post, 3 ft. long, 3" sq. firmly in the ground for 1/4 sec. cor. Mkd. 1/4 S on N and S faces, from which
A Cedar, 8" dia., bears S.10°W., 5 lks., mkd: 1/4 S BT.
A Fir, 18" dia., bears N.5°W., 20 lks., mkd: 1/4 S BT.

David Edwards - For: Seneca Jones Tmbr Co. - 3/2020 - C.S. File 65/105-11

Found - No original evidence could be found for the South 1/4 corner of section 16.
Set 1/4 corner by single proportion method.
Set - 5/8"x30" steel rebar with 2 1/2" diam. alum. cap stamped as per the 2009 BLM Manual and also stamped "LS 2339" and "2020".
New - An 11" dia. Fir scribed "1/4 S16 BT" bears N.49°E., 11.6 ft.
An 11" dia. Fir scribed "1/4 S21 BT" bears S.36°E., 8.8 ft.
6 ft steel posts are set 2 ft N.88°E. and S.88°W.