

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5016-7)

Set a Cedar post, 3 ft. long, 3" sq., firmly in the ground, for ¼ sec. cor., mkd on N & S face ¼ S; from which

A fir, 12" dia., bears S.25°E., 33 lks., mkd: ¼ S BT.

A cedar, 24" dia., bears N.45°W., 17 lks., mkd: ¼ S BT.

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12435)

Point for the ¼ sec. cor. of secs. 9 & 16, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:

T27S R3W

¼ $\frac{S \ 9}{S \ 16}$

1958

from which

A cedar, 16" dia., bears N.66°W., 18 lks., mkd: ¼ S9 BT.

A fir, 9" dia., bears S.7°E., 58 lks., mkd: ¼ S16 BT.

Fd. Ok by R. Geisler, 6/12/1986 C.S. File 63/34-29

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2300 surveyed March/April 2008 - (DCSO records Vol. 56 Pg 21835)

The ¼ sec. cor. of secs. 9 and 16, reestablished at proportionate by Corbin in 1958, monumented with an iron post, 2½" dia., firmly set, projecting 3" above the ground, with brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Corbin

A fir snag, 14" dia., bears S.7°E., 38.3 ft., with a healed blaze.

A cedar, 23" dia., bears N.66°W., 11.9 ft., with a healed blaze.

and a new bearing tree

A fir, 7" dia., bears S.2¾°W., 37.1 ft., mkd. ¼ S16 BT.

New bearing trees have a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

(See plat for bearings & distances of the lines)