

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5018)  
-----  
Set cedar post, 3 ft. long, 3" sq., firmly in the ground for 1/4 sec. cor. mkd 1/4 S on N & S faces, from which  
    A laurel, 6" dia., bears N.40°E., 6 lks., mkd: 1/4 S BT.  
    A laurel, 6" dia., bears S.85°E., 19 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - June 1957 - C.S. File 47/193  
-----  
Found snag of NE original BT, now 14" with good scribing (1/4S)  
Also found rotted base of stump of SE BT. Checks for bearing and distance.  
Set an iron pipe with brass cap at corner Mkd. 1/4 S4/9 T27S R3W County Surveyors Office, 1957.  
Blaze and scribe:  
    8" Cedar, S.4 1/2°E 22.0 ft mkd. 1/4 S9 CS BT.  
    9" Cedar, N.41 1/2°W., 14.0 ft Mkd. 1/4 S4 CS BT.  
Note - Corner under 12" Cedar log.

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2300 surveyed March/April 2008 - (DCSO records Vol. 56 Pg 21837)  
-----  
The 1/4 sec. cor. of secs 4 & 9, perpetuated by Byron, in 1957, from original evidence no longer in existence, monumented with an iron post, 1 1/4" dia., firmly set, projecting 1" above the ground, with brass cap (properly) mkd.  
from which the remains of bearing trees mkd. by Byron  
    A cedar, 12" dia., bears S.5°E., 21.9 ft., with no marks visible.  
    A sawed cedar stump, 12" dia., bears N.39 1/4°W., 14.0 ft., with no marks visible.  
and new bearing trees  
    A fir, 7" dia., bears N.61°E., 9.0 ft., mkd. 1/4 S4 BT.  
    A fir, 11" dia., bears S.27 1/2°E., 12.4 ft., mkd. 1/4 S9 BT.  
New bearing trees have a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.  
(See plat for bearings & distances of the lines)

Ron Quimby - Crew: N. Fromdahl, R Heichel & R Vincent - 12/2017 - C.S. File 65/101-14  
-----  
Found - 2 1/2" DCSO brass cap (properly marked)  
    10" Fir N.61°E., 9.0 ft. good scar.  
continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New -	14" Fir S.27°E., 12.4 ft. good scar, (rec. S.27½°E.)
	12" Fir S.65°W., 9.1 ft. scribed ¼ S9 BT.
	12" Fir N.64°W., 29.6 ft. scribed ¼ S4 BT.
Note -	Compass decl. 15½°E.

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Jeff Lorsung - 11/3/2020 - C.S. File 67/46-49

-----

Found OK  
Lat: 43.242225500                      Long: -123.059813595