TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 340700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 4; & 33 of T.26-3

Alias_____ Description_____
Alias_____ Description_____
Alias_____ Description_____
Alias_____ Description_____

Original - Addison R. Flint, Contract #56 dated March, 1855
(DCSO Records, Volume 10 Page 4351)

Set ¼ sec. post, from which
A Laurel 6" dia., bears N.85°E., 30 lks. dist.
A Laurel 5" dia., bears S.80°E., 22 lks. dist.

BLM survey by Harold Corbin, Group #350, survey Aug/Nov. 1958
(DCSO records, Volume 29 Page 12415)

Point for cor. at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long 2½" dia., 25" in the ground with brass cap mkd. T 26 S R 3 W

¼ S 33 / S 4

1958 from which
A Fir 60" dia., bears N.75¾°W., 153 lks. mkd. ¼ S33 BT.
A Cedar 67" dia., bears S.48¾°W., 560 lks. mkd. ¼ S4 BT.

Doug. County Surveyors Office - V. Tracy; M. Stone; J. Heritage - February 1966 - C.S. File 54/7-61

Found - 1958 Cad. Brass cap mkd. for corner.
60" D.Fir N.75¾°W., 101.0 ft. alive, scribe visible, pitched face.
67" Cedar S.48¾°W., 369.6 ft., now broken snag 12 ft. high, shows "¼ S3 BT", should be "S4".
New BT - 5" Laurel S.87°E., 119.2 ft. mkd. ¼ S4 CS BT.
This corner lies approx. 100 ft. east of bottom of small draw, course N.

Fd. OK by D. Edwards, 3/2007 - C.S. File 65/61-2

David Edwards - Crew: Brant Miller & Eric Sprinkle - 3/8/2016 - C.S. File 65/93-11

Found - Standard B.L.M. Brass Capped iron pipe.
A dead 9" dia. Madrone bears S.87°E., 119.2'
A 62" dia. Fir stump bears N.75¾°W., 101.0'
A six ft steel post is found 2 feet South.
New - A 13" dia. Fir scribed "¼ S33 BT" bears N.38°E., 19.7 ft.
A 13" dia. Fir scribed "¼ S4 BT" bears S.10°E. 8.5 ft
A six ft steel post is set 2 feet East.
Compass declination 15° East.

Fd. OK 12/2017 by R. Quimby C.S. File 65/101-12