

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5002)

Set cedar post, 3 ft. long, 3" sq., firmly in the ground for 1/4 sec. cor. mkd 1/4 S on E & W faces, from which
 A yew, 8" dia., bears N.40°W., 25 lks., mkd: 1/4 S BT.
 A maple, 6" dia., bears S.82°E., 9 lks., mkd: 1/4 S BT.

Thomas E. Shrum, Jr. - For: US Plywood Corp. - Dec. 1962 thru Jan. 1963 - C.S. File 51/254-12

Found - 3/4" Iron Rod - This iron rod was set by me from the Orig. BTs in 1955; subsequent logging destroyed all Orig. BTs.
I now scribe new BTs. referring to the iron rod.
Set - 22" Cedar Stump S.78°W. 24.2 ft Mkd: 1/4 S33 BT RE4287
 5" Hemlock, S.52°W. 52.6 ft. Mkd: 1/4 S33 BT RE4287
 12" Cedar N.19°E., 71.1 ft. mkd: 1/4 S34 BT RE4287

David Edwards - For: Seneca Jones Timber Co. - Feb. 2013 - M164-68

Found 1/4 corner per CS 51/254 (3/4" dia., IR) No BTs remain.
New BTs- 14" dia., alder bears S.57°E., 14.8 ft.
 9" dia., hemlock bears S.1°E., 33.4 ft.
 5" dia., hemlock bears N.78°W., 5.4 ft.
 6 ft. post is set 2' north.