

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5003)

Set cedar post, 4 ft. long, 4" sq., firmly in the ground for cor. to secs. 27, 28, 33, & 34, T27S R3W S27 on NE, S28 on NW, S33 on SW & S34 on SE faces with 3 notch on E & 1 notch on S edges, from which

A cedar, 6" dia., bears N.25°E., 26 lks., mkd: T27S R3W S27 BT.

A cedar, 12" dia., bears N.30°W., 36 lks., mkd: T27S R3W S28 BT.

A fir, 30" dia. bears S.45°W. 45 lks. mkd: T27S R3W S33 BT

A fir, 14" dia. bears S.35°E. 17 lks. mkd: T27S R3W S34 BT

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12428)

The cor. of secs. 27, 28, 33, & 34, perpetuated with an iron pipe, 1/2" dia., firmly set, 6" above ground, at record bearing and distance from the two remaining original BTs:

A fir, 48" dia., bears S.45°W., 45 lks., bark scribed T27S R3W R3W BT.

A cedar, 30" dia., bears N.30°W., 36 lks., with a healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 26", in the ground with brass cap mkd.

T27S	R3W
<u>S 28</u>	<u>S 27</u>
S 33	S 34
1958	

from which

A hemlock, 11" dia., bears N.20°E., 66 lks., mkd: T27S R3W S27 BT.

A fir, 8" dia. bears S.43°E., 71 lks. mkd: T27S R3W S34 BT

A cedar, 13" dia., bears S.35°W., 60 lks., mkd: T27S R3W S33 BT.

A cedar, 27" dia., bears N.32°W., 81 lks., mkd: T27S R3W S28 BT.

Deposit local corner material alongside iron post.

Douglas County Surveyors Office - Randall Smith & Stephen Flause - Jan. 13, 1997 - C.S. 64/71-7

Found - 3½" dia. Brass cap on a 2½" O.D. Iron pipe protrudes 5" above ground.

3/4" I.R. with "+" on top, bears N.24°E., .8'
continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

1/2" I.P. found in 1958 BLM Survey not visible
US CADASTRAL SURVEY

T27S R3W

S28|S27

S33|S34

1958

BUREAU OF LAND MANAGEMENT

49" Dia. 80' high D.Fir snag, with bark scribing visible, bears S.47°W. 32.5' (rec. S.45°W., 29.7' Dist falls short of BT) OBT.

36" Dia. Cedar, with a healed blaze, bears N.30°W., 25.3' (Rec. N.30°W., 23.8' fits well to face) OBT

No other OBT's found

27" Dia. Cedar, with a fully healed single blaze, bears S.32½°W., 41.5'. (Rec. S.35°W., 39.6' Dist. falls short of BT 1958 BLM).

27" Dia. 20' high Cedar snag, with an unhealed sing blaze, scribing visible "T27S R3W S28 BT", bears N.32°W., 53.5' (agrees with rec. 1958)

No other 1958 BLM BT's found

Per orig. notes, 14" Fir S.35°E., 11.2' per C.S. 35/19, 16" Yew S.35°E., 11.2', we find a 16" Dia. Yew with a partially healed blaze, no scribing visible, bears S.44°E., 11.2' OBT?

New - 11" Dia. D.Fir, double blazed and scribed "T27S R3W S34 CS BT", bears S.88°E., 34.9'.

12" Dia. D.Fir, double blazed and scribed "T27S R3W S27 CS BT", bears N.55½°E., 34.9'.

Fd. as per 1997 renewal, by D. Edwards - May 2012 - M163-57