TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 400220

PRIMARY CORNER DESCRIPTION S 1/16 Cor. bet. Secs. 27 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12428)

Point for the S1/16 sec. cor. of secs. 27 & 28
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked: S 1/16
S 28|S 27
1958
from which
A fir, 10" dia. bears N.13½°E., 26 lks. mkd: S 1/16 S27 BT
A chinquapin, 8" dia., bears S.13°W., 38 lks., mkd: S 1/16 S28 BT.

Douglas County Surveyors Office - Randall Smith & Stephen Flause - Jan. 23, 1997 - C.S. 64/71-8

Found - 3¼" Brass cap on a 2½" O.D. iron pipe. protrudes 4" above ground. Orig. Cor. U.S. CADASTRAL SURVEY
S 1/16
S28|S27
1958
BUREAU OF LAND MANAGEMENT
10" now 12" dia. 2' high rotted D.Fir stump with scribing "S 1/16 S27", bears N.13½°E., 17.2'. (agrees with rec.) OBT.
8" now 14" dia. Dead Chinquapin, with a partially healed single blaze, no scribing visible, bears S.15°W., 25.1' (Rec. S.13°W., 25.1') OBT.
New BTs- 11" dia. D.Fir, double blazed and scribed "S 1/16 S27 CS BT", bears N.5°E., 16.6'.
7" dia. Hemlock, double blazed and scribed "S 1/16 S28 CS BT", bears N.59°W., 34.4'.
10" dia. Madrone, bark scribed "S 1/16 S27 CS BT", bears N.81°E., 25'.

David Edwards - For: Seneca Jones Timber - May 2012 - M163-57

Found - 12" Fir, N.5°E., 16.6'
8" Hemlock, N.59°W., 34.4' } Both w/healed blazes
Madrone N.81°E., is dead.