

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5005)

Set laurel post, 3 ft. long, 3" sq., firmly in the ground for 1/4 sec. cor. mkd 1/4 S on E & W faces, from which
 A fir, 6" dia., bears S.62°W., 62 lks., mkd: 1/4 S BT.
 A laurel, 12" dia., bears N.70°E., 21 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - S. Bilow - Oct. 11-14-15 1957 - C.S. File 49/14-4

Found - Orig. 6" now 16" R.Fir BT. S.62°W., 40.9 ft recently opened. I find good scribing "S".
 I can find no evidence of Original NE BT.
Set Brass Cap at cor mkd 1/4 S21|S22 T27S R3W County Surveyors Office, 1957.
New BTs- 24" R.Fir S.86°W., 31.3 ft. scribed 1/4 S21 CS BT.
 20" R.Fir S.82°E., 33.7 ft. scribed 1/4 S22 CS BT.

BLM dependent resurvey James Jelley, Cadastral Surveyor under Group #995 surveyed Sept 1979 (DCSO Vol 42 Pages 16475-6)

The 1/4 sec. cor. of secs. 21 & 22, perpetuated & recorded by Byron, in 1957, monumented with an iron post, 1 1/4" dia., firmly set, projecting 18" above ground, with brass cap (properly) mkd.
from which the remains of an orig. BT
 A sawed fir stump, 16" dia., bears S.62°W., 62 lks., no marks visible.
and the remains of a BT mkd. by Byron
 A sawed fir stump, 22" dia., bears S.82°E., 51 lks., no marks visible.
Corner is located in logged area.