

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5006)

Set fir post, 4 ft. long, 4" sq., firmly in the ground for cor. to secs. 15, 16, 21, & 22, marked T27S S 15 on NE, R3W S 16 on NW, S 21 on SE, S 22 on SE faces, with 3 notches on E & S edges; from which

- A fir, 14" dia. bears N.25°E. 22 lks. mkd: T27S R3W S15 BT
- A cedar, 30" dia., bears N.65°W., 55 lks., mkd: T27S R3W S16 BT.
- A maple, 8" dia., bears S.22°W., 50 lks., mkd: T27S R3W S21 BT.
- A laurel, 14" dia., bears S.70°E., 26 lks., mkd: T27S R3W S22 BT.

BLM remonumentation of a corner by Timothy J Moore, Cadastral Surveyor under Group No. 1000 surveyed Nov. 2000- (DCSO records Vol. 58 Pages 23323-5)

The cor. of secs. 15, 16, 21 & 22, determined at record bearing and distance from the remains of the original NE BT.

- A roothole, with a high stumped wind blown fir snag, 36" dia., alongside, bears N.25°E., 14.5 ft., with scribe marks 5 BT and other illegible marks visible on a weathered bark blaze face down.
- A roothole, bears S.70°E., 17.2 ft.
- A roothole, bears S.26°W., 33 ft. (Record, S.22°W.)
- A roothole, bears N.65°W., 36.3 ft.

At the corner point
Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd.

T27S	R3W
<u>S 16</u>	<u>S 15</u>
<u>S 21</u>	<u>S 22</u>
2000	

from which new bearing trees

- A fir, 20" dia, bears N.71°E. 27.9 ft. mkd T27S R3W S15 BT
- A fir, 6" dia, bears S.52½°E., 25.4 ft., mkd. X BT.
- A fir, 18" dia, bears S.20°W. 32.0 ft. mkd T27S R3W S21 BT
- A fir, 19" dia, bears N.58½°W. 27.1 ft mkd T27S R3W S16 BT

Deposit a magnet in a white plastic case at the base of the stainless steel post.
The corner is located on a S. slope.

Fd 3/2016 by R Ward C.S. File 65/92-5

continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Gerald Nygren - For: Seneca Jones Timber Co - 5/2016 - M172-2

Found - 2000 BLM brass cap & BTs per rec. 2000 rec. BTs:
20" Fir, now 24" bears N.71°E., 27.9' healed face
6" Fir, now 7" bears S.52°30'E., 25.4' healed face
21" cedar (rec. 18" fir) bears S.20°'45'W., 32.0'
healed face
19" fir bears N.58°30'W., 27.1 healed face
Galvanized metal post bears West, 1.0'

Fd. As per M172-2 3/2020 by D Edwards - CS 65/105-11