

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5007)

Set cedar post, 4 ft. long, 4" sq., firmly in the ground for cor. to secs. 9, 10, 15, & 16, marked T27S R3W S10 on NE, S9 on NW, S16 on SW, and S15 on SE, faces with 4 notches on the S & 3 on the E edges, from which
A fir, 10" dia. bears N.23°E. 17 lks. mkd: T27S R3W S10 BT
A hemlock, 6" dia., bears N.64°W., 6 lks., mkd: T27S R3W S9 BT.
A fir, 24" dia. bears S.85°W. 52 lks. mkd: T27S R3W S16 BT
A cedar, 20" dia., bears S.84°E., 69 lks., mkd: T27S R3W S15 BT.

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12434-5)

The cor. of secs. 9, 10, 15, & 16, determined at record bearing & distance from the two remaining original BTs.
A fir, 25" dia., bears N.23°E., 17 lks., with an opened blaze, no scribe marks visible.
A hemlock, 18" dia. bears N.64°W. 6 lks. with scribe marks R S & other illegible marks on an opened & rotted blaze
At the corner point
Set an iron post, 28" long, 2½" dia., 26" in the ground with brass cap mkd.
T27S R3W
S 9 | S 10
S 16 | S 15
1958

from which
A hemlock, 8" dia., bears N.69¼°E., 130 lks., mkd: T27S R3W S10 BT.
A hemlock, 13" dia., bears S.42°E., 56 lks., mkd: T27S R3W S15 BT
A hemlock, 13" dia., bears S.18½°W., 98 lks., mkd: T27S R3W S16 BT.
A cedar, 25" dia. bears N.89°W. 95 lks mkd: T27S R3W S9 BT

David Edwards - 5/2007 - M153-3

Found - (BLM) Brass cap
36" cedar N.89°W., 62.7', with healed blaze.
New - 4" Hemlock S.52½°E., 9.9'
8" Fir S.57½°W., 7.3'
6' steel post north 2'

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2300 surveyed March/April 2008 - (DCSO records Vol. 56 Pg 21831)

At the cor. of secs. 9, 10, 15, and 16, remonumented by Corbin in 1958, from original evidence no longer in existence, perpetuated by Edwards, in 2007, monumented with an iron post, 2½" dia., firmly set, projecting 3 ins. above the ground, with brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Corbin

A roothole bears S.18½°W., 64.7 ft., alongside of which is a decayed hemlock trunk, size indeterminate, with no marks visible.

A cedar, 40" dia., bears N.89°W., 62.7 ft., with a healed blaze.

and the bearing trees mkd. by Edwards

A fir, 5" dia., bears S.49¼°E., 9.9 ft., with scribe marks T27 R3 S15 BT visible on an open blaze.

A fir, 9" dia., bears S.58½°W., 7.3 ft., with scribe marks T27 R3 S16 BT visible on an open blaze.

and a new bearing tree

A fir, 7" dia. bears N.74¾°W., 33.8 ft. mkd T27S R3W S9 BT
New bearing trees have a 2 1/2 inch x 1/4 inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

(See plat for bearings & distances of the lines)

Gerald Nygren - For: Seneca Jones Timber Co - 5/2016 - M172-2

Found - 1958 BLM brass cap & BTs per rec.
25" cedar, now 40" bears N.89°W., 62.7' healed face, 1958.

4" Hemlock, now 5" (5" fir per USBLM 2008) bears S.49°15'E., 9.9' healed face

8" RR, now 11" bears S.58°30'W., 7.3' healed face, 2007

7" D.Fir, now 9" bears N.74°45'W., 33.8' healed face, 2008

Galvanized metal post bears north, 0.20'