

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4; 33 & 34 of T26-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Addison R. Flint, Contract #56 dated March, 1855  
(DCSO Records, Volume 10 Page 4351)

-----  
Set post, cor. to secs. 33, 34, 3 & 4, from which  
A Pine, 16" dia., bears S.64°E., 55 lks. dist.  
A Pine 16" dia., bears N.14°W., 70 lks. dist.  
A Red Fir 25" dia., bears N.75°E., 54 lks. dist.  
A Red Fir 26" dia., bears S.75°W., 50 lks. dist.

-----  
Bureau of Land Management survey by Harold D. Corbing under  
Group #350. Survey Aug/Nov. 1958 (DCSO records, Volume 29  
Page 12414)

-----  
Cor. determined at record distance from the remains of the  
original bearing trees:

A Fir stump 42" dia., bears N.78°E., 54 lks. dist. with  
a healed blaze. (Rec. bearing N.75°E.)  
A stump hole, with roots and bark of a Pine, bears  
S.64°E., 55 lks. dist.  
A Fir stump 36" dia., bears S.78°W., 50 lks. dist., no  
marks visible. (Rec. bearing S.75°W.)  
A down and rotted Pine 20" dia., bears N.11°W., 70 lks.  
dist., no marks visible. (Rec. bearing N.14°W.)

At the corner point

Set an iron post 28" ling, 2½" dia., 24" in the ground with  
brass cap mkd.

T 26 S R 3 W  
S 33 | S 34  
S 4 | S 3  
T 27 S

1958

from which

A Cedar 13" dia., bears N.32¾°E., 47 lks. dist., mkd.  
T26S R3W S34 BT.  
A Fir 9" dia., bears S.47¼°E., 15 lks. dist., mkd. T27S  
R3W S3 BT.  
A Fir 10" dia., bears S.68°W., 17 lks. dist., mkd.  
T27S R3W S4 BT.  
A Fir 11" dia., bears N.45°W., 17 lks. dist., mkd. T26S  
R3W S33 BT.

-----  
Doug. County Surveyors Office - Vernon Tracy; Mike Stone; Jack  
Heritage - Feb. 1966 - C.S. File 54/7-57

(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Found - 1958 Cadastral Brass cap mkd. for section corners.  
13" Cedar N.32 $\frac{3}{4}$ °E., 31.0 ft. scribed T26S R3W S34  
BT. Alive.  
9" D.Fir S.47 $\frac{1}{4}$ °E., 9.9 ft., scribe visible on  
pitched face.  
10" D.Fir S.68°W., 11.2 ft. pitched & almost healed  
blaze.  
11" D.Fir N.45°W., 11.2 ft., down & dead, scribing  
visible.  
New BT - 9" D.Fir N.18 $\frac{1}{2}$ °W., 35.5 ft. mkd. T26S R3W S33 CS BT.  
This corner lies approx. 120 ft. east of logging road, course  
NE and SW in young fir, cedar and laurel.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral  
Surveyors, under Group #1189, surveyed May/July 1984 - (DCSO  
records Vol. 47 Page(s) 17961)

-----  
The Sec. Cor., monumented with an iron post 2 $\frac{1}{2}$ " dia., firmly  
set, projecting 6" above ground with brass cap mkd. in 1958  
from which the remains of the original bearing trees:

A Fir stump 48" dia., bears N.78°E., 54 lks. dist. with  
fragmentary scribe marks visible on opened blaze.

A Fir stump 40" dia., bears S.78°W., 50 lks. dist. with  
healed blaze.

and the remains of bearing trees mkd. by Corbin:

A Cedar 15" dia., bears N.32  $\frac{3}{4}$ °E., 47 lks. dist. with  
fragmentary scribe marks visible on partially healed  
blaze.

A Fir 10" dia., bears S.47 $\frac{1}{4}$ °E., 15 lks. dist. with healed  
blaze.

A Fir snag 11" dia., bears S.68°W., 17 lks. dist., with  
healed blaze.

A root hole with down Fir alongside 12" dia., bears  
N.45°W., 17 lks. dist., with scribe marks T26S R3  
S33 visible on partially healed blaze.

and new bearing trees:

A Pine 5" dia., bears S.12°W., 40 lks. dist. mkd. X BT.

A Cedar 13" dia., bears N.88°W., 52 $\frac{1}{2}$  lks. dist. mkd. T26S  
R3W S33 BT.