

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by S.C. Flint, Contract #454, dated June 19, 1882
- (DCSO records Vol. 12 Page(s) 4977)

Set Laurel post 3 ft. long, 3" sq., firmly in the ground for
the ¼ sec. cor. mkd. S C ¼ S on N. face, from which
A Fir 36" dia., bears S.40°E., 48 lks. dist. mkd. S C ¼ S
BT.
A Fir 32" dia., bears N.45°W., 36 lks. dist. mkd. S C ¼ S
BT.

Survey by Thomas E. Shrum, Jr. - For: U.S. Plywood Inc. -
April 1963 - C.S. File 51/254-19

Found - 4" x 4" x 6 ft. Cedar post.
D.Fir stump N.45°W., 24.0 ft., burned off.
D.Fir stump S.40°E., 26.0 ft., burned off.
Set 2½" aluminum cap, from which
10" Cedar N.34¼°W., 30.9 ft. mkd. ¼ SC S34 BT.
8" Madrone N.63°W., 35.2 ft. mkd. ¼ SC S34 BT.

David Edwards - For: Seneca Jones Timber Co. - Feb. 2013 -
M164-68

Found - 3/4" I.R. with alum cap.
An 18" dia., cedar N.32½°E., 29.0' (N.34¼°W., 30.9')
A 12" dia., madrone with healed blaze bears N.63°W.,
35.2'
Set - A 6 ft. steel post 2 ft. north.