

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5003-4)  
-----

Set laurel post, 3 ft. long, 3" sq., firmly in the ground for 1/4 sec. cor. mkd 1/4 S on N & S faces, from which  
 A fir, 10" dia., bears N.10°W., 18 lks., mkd: 1/4 S BT.  
 A fir, 6" dia., bears S.30°E., 12 lks., mkd: 1/4 S BT.

---

Thomas E. Shrum, Jr. - U.S. Plywood Corp. - Dec. 1962 thru Jan. 1963 - C.S. File 51/254  
-----

Found - 3/4" iron rod.  
 10" D.Fir N.10°W., 11.9 ft. (down)  
 Set - 2 1/2" Alum. cap.  
 8" D.Fir S.33 1/2°E., 22.4 ft. mkd: 1/4 S34 BT.  
 11" D.Fir N.65°E., 36.0 ft. mkd: 1/4 S27 BT.

---

Mark Heimburger - For: Glide Lumber - Nov. 1996 - M126-11  
-----

No monument found.  
 Established cor. location from:  
 14" fir stump bears S.33°E., 22.4 ft. with visible blaze.  
 16" fir stump bears N.65°E., 36.0 ft with visible scribes.

---

Douglas County Surveyors Office - Randall Smith & Stephen Flause - Mar. 3, 1997 - C.S. 64/71-13  
-----

Found - Hub & Tack from Heimburger ren., no monuments found.  
 8" now 15" dia. 1' high D.Fir stump with a fully healed blaze, bears S.29°E., 22.4' (rec. S.33°E., 22.4').  
 11" now 20" dia. 1' high D.Fir stump with an opened blaze scribing visible "T", bears N.65°E., 36'.  
 20" dia. 12' high D.Fir snag with previously opened blazes, scribing visible "BT", bears N.18°W., 14.5', Orig. NW? noted as down in 1963 may have been stood up by logging, roots on top of ground. Orig. rec. N.10°W., 11.9'.  
 Set - 2 3/8" dia. Brass cap on a 1 3/8" O.D. by 32" long iron pipe set at position on Hub & Tack. BC/IP protrudes 6" above ground. Cap marked:  
 DOUGLAS COUNTY SURVEYORS  
 T27S  
 1/4 S 27 R  
 S 34 3  
 1997 W  
 OFFICE

cont. next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

New BTs- 5" dia. pistol butt D.Fir, double blazed and scribed "¼ S27 CS BT", bears N.33°E., 8.5, to center of plumb trunk.  
3" dia. D.Fir, double blazed and scribed "X BT", bears S.85°W., 19.6'.  
5" dia. W.Fir double blazed and scribed "¼ S27 CS BT", bears N.58½°W., 42.5'.  
7" dia. D.Fir, double blazed and scribed "¼ S34 CS BT", bears S.27°E., 31.6'.

Fd. as per M126-11 & 1997 renewal, by D. Edwards - May 2012 - M163-57