

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5005)

Set oak post, 3 ft. long, 3" sq., firmly in the ground for ¼ sec. cor. mkd ¼ S on N & S faces, from which
 A Fir, 6" dia., bears S.48°W., 40 lks., mkd: ¼ S BT.
 A W.Oak, 24" dia., bears S.60°E., 42 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John Powell - July 31, 1970 - C.S. File 54/40-191

Reported as not found.
Fd. Lg Oak previously opened, tree rotted out - some other Oaks in area opened some with no results.

BLM dependent resurvey James E. Jelley, Cadastral Surveyor under Group #995 surveyed Sept. 1979 (DCSO Vol 42 Page 16473)

The ¼ sec cor of secs. 22 & 27 reestablished by proportionate measurement & recorded by Shrum Jr., in 1978*, and is accepted as the best available evidence of the position of the original corner, monumented with an iron post, 1" dia. firmly set, projecting 6" above ground, with aluminum cap mkd
 T27S R3W
 S 22 ¼
 S 27
from which
 A fir, 5" dia., bears N.22°E., 12 lks., mkd. ¼ S22 BT.
 A fir, 5" dia., bears S.59°W., 18 lks., mkd. ¼ S27 BT.
* We do not have a record of a 1978 survey by Shrum in this area. - DCSO JC 4/28/2008

Fd. Ok by M. Heimbürger, 11/1996 - M126-11