

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 479100

PRIMARY CORNER DESCRIPTION C C for Secs. 2 & 3 only, T28-3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by S.C. Flint, Contract #459, dated June 19, 1882
(DCSO records Vol. 13 Page(s) 5543)

Intersect the N. bdy. of Tsp. 62 lks. W. from the standard
cor. to secs. 34 and 35, Set a post 4 ft. long, 4" sq., 24"
in the ground for CC to secs. 2 and 3 and marked CC T28S R3W
on S., S2 on E. and S3 on W. faces with 4 notches on W. and
2 notches on E. faces, from which

A Maple 7" dia., bears S.40°E., 11 lks. dist. mkd. T28S
R3W S2 BT.

A Fir 24" dia., bears S.8°W., 4 lks. dist. mkd. T28S R3W
S3 BT.

A Fir 48" dia., bears N.42°W., 85 lks. dist. mkd. T27S R3W
S34 BT.

Douglas Co. Surveyors Office - Randall Smith and Stephen
Flause, crew - Feb. 19, 1997 - C.S. File 64/71-17

CONDITION REPORT ONLY

Found - 2½" alum. cap on a 1"O.D. Iron pipe protrudes 16"
above ground. Set by Thomas Shrum, date unknown,
not of record.

No original BTs found.