

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

<p>GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 4997)</p> <p>-----</p> <p>Set cedar post, 3 ft. long, 4" sq., firmly in the ground for 1/4 sec. cor. mkd 1/4 S on E &amp; W faces, from which A fir, 40" dia., bears S.55°E., 5 lks., mkd: 1/4 S BT. A fir, 14" dia., bears N.70°W., 30 lks., mkd: 1/4 S BT.</p>
<p>Thomas E. Shrum, Jr. - For: US Plywood, INC - April 1963 - C.S. File 51/254-19</p> <p>-----</p> <p>Found - 3/4" iron rod. 48" D.Fir stump, S.55°E., 3.3 ft. (orig. BT), 4"x6" alum. tag 1952 27" D.Fir S.48°W., 19.0 ft., 4"x6" alum tag, 1952.</p> <p>Set - 2 1/2" alum. cap. 11" W.Fir S.73°W., 18.1 ft. mkd: 1/4 S27 BT. 6" Yew N.40°E., 38.6 ft. mkd: 1/4 S26 BT.</p>
<p>Ronald G. Geisler, LS 1988 - For: Champion International Cor. - Jan. 1984 - M95-77 &amp; C.S. 58/278</p> <p>-----</p> <p>Found - 1963 Alum. cap and iron pipe set by RE 4287. 1963 50" fir stump bears S.51°E., 6.4 ft. (Rec. S.55°E. 3.3 ft. to face). No scribing found. (orig.) 15" yew bears N.40°E., 36.6 ft. (Rec 38.6 ft) Scribe marks visible (1963) 27" fir stump bears S.52°W., 22.0 ft. No scribing evident. (unrecorded)</p> <p>New BT - 8" fir bears N.82°W., 37.2 ft. scribed: 1/4 S27 BT.</p>
<p>FD. Ok by Mark Heimbürger 11/1996 - M126-11</p>
<p>David Edwards - For: Seneca Jones Timber - May 2012 - M163-57</p> <p>-----</p> <p>Found - Alum. cap per RE 4287 15" Fir N.82°W., 37.2' Yew is down</p> <p>New BT - 6" Fir scribed "1/4 S26 BT" brs. S.15°E., 12.2 ft.</p>
<p>Douglas Co. Surveyors Office - Crew: Stephen Flaue &amp; Jeff Lorsung- 2/12/2019 (Filed 11/17/2021) - C.S. File 67/50-12</p> <p>-----</p> <p>Found - A 1" o.d. iron pipe, firmly set, projecting 19" above the ground with a 2 1/2" dia. aluminum cap (Properly) marked Original BTs by Flint in 1882 - continued next page</p>

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 48"x3.5' tall D.Fir stump bears S.55°E., 5.0 ft.  
(3.3' Record distance was a face measurement)  
BTs by Shrum in 1963 -  
A 27"x2.5' tall rotted D.Fir stump bears S.52°W.,  
22.0 ft.  
BTs by Geisler in 1984 -  
A 23"x3' tall D.Fir stump bears N.82°W., 37.2 ft.  
w/fully healed blaze.  
BTs by Edwards in 2012 -  
A 7"x2' tall shattered D.Fir stump bears S.16°E.,  
12.2 ft., w/partial visible scribing.  
New - A 8" Magnail placed in the top center of a 24"x1.5'  
tall sawn D.Fir stump bears N.3°E., 68.5 ft.  
A 8" Magnail placed in the top center of a 24"x1'  
tall sawn D.Fir stump bears S.32°E., 13.0 ft.  
A 15" D.Fir bears S.70¼°W. 50.0 ft scribed "¼S27CS"  
"BT"  
A 8" Magnail placed in the top center of 1984  
Geisler stump described above.  
Note - The corner falls near an old skid road on a clear  
cut approximately 20 ft. from the cutting corner.  
All BTs have BT Tags attached. All new BTs have  
double blazed faces with bearing measured to the  
center of the trees at the root crown and  
distances measured to a 4" Magnail in the side  
and center of the root crown.  
Compass declination 14¼°E.  
Geodetic coordinates  
LAT: 43°05'27.988396574"N LONG: 123°37'21.303674470"W  
NAD 83 SOURCE: GeoXT6000