

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 4997)

-----  
Set cedar post, 4 ft. long, 4" sq., firmly in the ground for cor. to secs. 22, 23, 26, & 27, marked T27S S 23 on NE, R3W S 22 on NW, S 27 on SW, S 26 on SE, with 2 notches on E & S edges; from which

A laurel, 22" dia., bears N.70°E., 69 lks., mkd: T27S R3W S23 BT.

A fir, 24" dia. bears N.23°W. 50 lks. mkd: T27S R3W S22 BT  
A W.Oak, 14" dia., bears S.72°W., 225 lks., mkd: T27S R3W S27 BT.

A fir, 18" dia. bears S.52°E. 90 lks. mkd: T27S R3W S26 BT

Douglas Co. Surveyors Office - Ben B Irving, Co. Surveyor - Milo Godfrey - Lester Kershner - May 14, 1947 - C.S. File 38/187 & M16-78

-----  
At which point I found. one of the orig. BTs standing & in good shape with scribe marks plainly legible

A fir 46" dia. bearing N.23°W. 50 lks. Careful measurements disclosed the remnants of 2 other of the orig. BTs viz, charred roots and stump hole of the laurel N.70°E 69 lks. and the fir stump burned off level with the ground S.52°E., 90 lks. Measuring in from these points, we located the hole which the orig. corner stake stood and at the point set a 1"x36" iron pipe, with a brass cap stamped "County Surveyors Office T 27 S R 3 W S 22, S 23, 3 26, S 27" for the corner.

BLM dependent resurvey James E. Jelley, Cadastral Surveyor under Group #995 surveyed Sept. 1979 (DCSO Vol. 42 Page(s) 16472-3)

-----  
Beginning at the cor. of secs. 22, 23, 26, & 27, perpetuated & recorded by Byron, in 1957, monumented with an iron post, 1½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd. \*per BLM letter dated 2/13/1984 Should

be 1947 - Ben B. Irving Set cap VL from which the remaining orig. BT, remarked by Byron

A fir 44" dia., bears N.27½°W., 50 lks., with orig. fragmentary scribe marks visible on bark blaze & scribe marks T27S R3W S22 CS BT visible on bark blaze. (Rec. N.23°W.)

and the remains of bearing trees mkd. by Byron

A fir snag, 18" dia., bears N.70°E., 73½ lks., with fragmentary scribe marks visible on open blaze.

A fir snag, 20" dia., bears S.74°E., 54½ lks., with fragmentary scribe marks visible on open blaze. cont.

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing trees

An Oak, 10" dia., bears N.71°E., 12½ lks., mkd: T27S R3W S23 BT.

An Oak, 10" dia., bears S.74¾°E., 6½ lks., mkd: T27S R3W S26 BT.

An Oak, 8" dia., bears S.41¾°W., 69 lks., mkd: T27S R3W S27 BT.

An Oak, 13" dia., bears N.34¾°W., 28 lks., mkd: T27S R3W S22 BT.

Fd. & used on BLM Dependent resurvey by Boyd W. Peterson & Mark D. Dixon, Cadastral Surveyors, under Group #1268, surveyed May/Sept 1985 - (DCSO records Vol. 48 Pages 18214-5)

FD. Ok by Mark Heimburger, 11/1996 - M126-11