

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5000)

Set cedar post, 3 ft. long, 3" sq., firmly in the ground for 1/4 sec. cor. mkd on E & W faces, 1/4 S from which
 A chincapin, 10" dia., bears S.25°W., 9 lks., mkd: 1/4 S BT.
 A cedar, 10" dia., bears S.65°E., 17 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - Ben B. Irving, County Surveyor
- Witnesses: H.C. Carey & R.C. Kerchner - April 4, 1945 -
C.S. File 38/46

Set 6x8x16" stone.
60" Fir N.60°E., 3.0 ft.
20" Fir N.75°W., 18.8 ft.

Thomas E. Shrum, Jr - US Plywood, Inc. - Jan 22, 1965 - C.S.
File 51/254-24

Found - Stone 6"x8"x16", on South Side. 1945
 60" Fir Stump N.60°E. 3 ft
 22" Fir Stump N.75°W. 18.9 ft.
Set - 2" ALUMINUM CAP
 6" Madrone S.25°W. 18.5 ft.
 8" Cedar N.32°E. 93.1 ft.

Fd. Ok 6/2006 by D. Edwards, M150-67

Ken Hoffine - For: Lone Rock Timber Co. - Aug. 2008 - C.S.
File 65/63-30

Found - 1957 Douglas County cap.
 28" cedar bears N.67°E., 28.9 ft (record N.66°E,
 28.71 ft) healed face and tag
 32" W.Fir bears S.69½°E, 13.6 ft (record S.68°E,
 12.54 Ft) healed face and tag
 22" Fir snag bears S.12½°E., 51.1 ft (record S.13°E.
 51.48 ft) healed face and tag
 33" cedar bears S.54½°W., 18.8 ft (record S.58°W.,
 19.14 ft) healed face and tag
 30" cedar bears N.42¾°W., 77.4 ft (record N.43°W.,
 77.22 ft) healed face and tag
 1958 BLM Brass Cap bears N.58°30'E., 0.32 FT
Corner lies in mound of stones and approximately 150 feet
West of rock road.

continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Gerald Nygren - For: Seneca Jones Timber Co - 5/2016 - M172-2

Found - 2" aluminum cap stamped "RE 4287" & BTs per C.S.
File 51/254,
60" Fir, now rotten stump bears N.60°E., 3.0' No
visible marks. 1945
20" Fir, now 22" stump pushed over bears N.75°W.,
18.9' no visible marks. 1945
6" Madrone, now 14" sawed stump 6' tall bears
S.25°W., 18.5', Healed face with tag. 1965
8" Cedar, now 24" sawed stump 6' tall bears N.32°E.,
93.1' healed face with tag. 1965
Set galvanized metal post north, 2.0'