

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor Secs 10, 11, 14, & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and county surveyor's bearing trees:

A cedar, 12" dia bears N.66°E. 43½ lks with a healed blaze

A cedar, 12" dia bears S.53°W., 29 lks with a healed blaze

At the corner point

Set an iron post, 28" long, 2½" dia., 26" in the ground, with
brass cap mkd.

T 27 S R 3 W

S 10 | S 11

S 15 | S 14

1958

from which

A fir, 19" dia., bears N.41½°E., 88 lks., mkd. T27S R3W
S11 BT.

A fir, 12" dia. bears S.13°E., 78 lks mkd. T27S R3W S14 BT

A fir, 10" dia., bears S.11°W., 124 lks. dia., mkd. T27S
R3W S15 BT.

A fir, 13" dia., bears N.59½°W., 58 lks., mkd. T27S R3W
S10 BT.

BLM dependent resurvey by Lance J. Bishop & Wayne L. Rogers,
Cadastral Surveyors, under Group #1189, surveyed May/July
1984 - (DCSO records Vol. 47 Page(s) 17956-7)

The cor. of secs, 10, 11, 14, & 15, monumented with an iron
post, 2½" dia., firmly set, projecting 3", above ground, with
brass cap (properly) mkd.

from which the remains of the original BTs

A fir, 30" dia., bears S.68°E., 19 lks., with healed blaze

A root hole, with down fir alongside, 44" dia., bears
N.38°W., 54 lks., no marks visible.

and BTs mkd. by Ben B. Irving, County Surveyor, in 1945

A cedar, 21" dia., bears N.66°E., 43½ lks., with healed
double blaze.

A cedar, 25" dia., bears S.58°W., 29 lks., with healed
double blaze. (Rec S.53°W)

and a bearing tree mkd. by Corbin

A fir, 22" dia., bears S.13°E., 78 lks., with healed blaze.

and a new bearing tree

A cedar, 19" dia., bears N.43°W., 117 lks., mkd T27S R3W
S10 BT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral
Surveyor, under Group No. 2258, Surveyed April/June 2009 -
(DCSO records Vol. 57 Page(s) 22672-3)

The cor of secs 10, 11, 14 & 15 monumented with an iron post,
2½" dia., firmly set, projecting 3" above a collar of stone
(alongside of which is an iron post, 1¼" dia., firmly set,
bent SW., projecting 7" above ground, ... Cont. next pg.

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

.... with brass cap (properly) mkd.
from which the remains of the original bearing trees
A fir, 32" dia., bears S.68°E., 12.5 ft., with a healed blaze.
A roothole bears N.38°W., 35.6 ft., alongside of which is an uprooted, sawed, decayed fir stump, size indeterminate, with no marks visible.
and bearing trees mkd. by Irving, in 1957
A cedar, 29" dia., bears N.66°E., 28.7 ft., with a healed blaze.
A cedar, 32" dia., bears S.58°W., 19.1 ft., with a healed blaze.
and the remains of a bearing tree mkd. by Corbin
A decayed fir snag, 23" dia., bears S.13°E., 51.5 ft. with a healed blaze.
and a bearing tree mkd. by Bishop and Rogers
A cedar, 29" dia., bears N.43°W., 77.2 ft., with a healed blaze.
Corner is located on an E. slope.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 11/3/2020 (Filed 11/18/2021) - C.S. File 67/51-3

Found - 2½" IP with ¾" brass cap proj. 5" above ground (properly marked) with DCS0 2½" brass cap along side proj. 8", leans SW
30" Fir snag S.68°E., 12.5 ft. (healed blaze in fallen bark) (OBT)
A roothole N.38°W., 35.6 ft. uprooted sawed, decayed Fir stump alongside, size indeterminate, no marks visible. (OBT)
30" R.Cedar N.66°E., 28.7 ft. healed blaze. 1957
37"x6' high R.Cedar stump S.58°W., 19.1 ft. healed blaze. 1957
32" R.Cedar N.41½°W., 77.2 ft. (rec. N.43°W.) healed blaze. BLM 1984
New - 8" MAG NAIL in top center 14"x1' tall D.Fir stump S.17½°E., 29.6 ft