

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Sam C. Flint, Under Contract #454, dated June 19, 1882 (DCSO Records Vol. 12 Page(s) 5001-2)

 Set cedar post, 3 ft. long, 4" sq., firmly in the ground for 1/4 sec. cor. mkd 1/4 S on E & W faces, from which
 A fir, 6" dia., bears S.80°W., 38 lks., mkd: 1/4 S BT.
 A fir, 36" dia., bears S.30°E., 34 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Harold D. Corbin, Cadastral Surveyor under Group No. 350 & 412, surveyed Aug./Nov. 1958 - (DCSO records Vol. 29 Page(s) 12423)

 Point for the 1/4 sec. cor. of secs. 10 & 11, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 1/2" dia., 26" in the ground with brass cap marked:
 T27S R3W
 1/4
 S 10 | S 11
 1958
 from which
 A fir, 10" dia., bears N.59 3/4°E., 44 lks., mkd: 1/4 S11 BT.
 A fir, 7" dia., bears S.52°W., 66 lks., mkd: 1/4 S10 BT.

BLM dependent resurvey by Lance J. Bishop & Wayne L. Rogers, Cadastral Surveyors, under Group #1189, surveyed May/July 1984 - (DCSO records Vol. 47 Page(s) 17969)

 The 1/4 sec. cor. of secs. 10 & 11, monumented with an iron post, 2 1/2" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.
 from which the remains of bearing trees mkd. by Corbin
 A fir, 15" dia., bears N.59 3/4°E., 44 lks. with healed blaze
 A fir stump, 13" dia., bears S.52°W., 66 lks., with healed blaze.
 and a new bearing tree
 A fir, 9" dia., bears S.50 3/4°W., 74 lks., mkd. 1/4 S10 BT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2258, Surveyed April/June 2009 - (DCSO records Vol. 57 Page(s) 22673)

 The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 2 1/2" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.
 from which the remains of bearing trees mkd. by Corbin
 A fir, 20" dia., bears N.59 3/4°E., 29.0 ft., with a healed blaze.
 continued next page

TOWNSHIP 27 RANGE 03 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed fir stump, 13" dia., bears S.52°W., 43.6 ft. with a healed blaze.
and a bearing tree mkd. by Bishop and Rogers
A fir, 13" dia., bears S.50¾°W., 48.8 ft., with a healed blaze.
Corner is located on a N. slope, at the intersection of dilapidated barbed wire fence lines extending N and W; and 80 ft. N. of a dirt road, 13 ft. wide, bears N.45°E. and S.45°W.

Bartt Heichel - For: Linnea Torkeisen - 8/2023 - M182-60

Found - 2½" dia. iron post, projecting 8" above ground, with brass cap properly marked (1958 BLM) From which:
21" Fir (rec. 20") with healed blaze bears N.59°45'E., 29.0'
13" Rotten sawed Fir stump, 1.5 ft tall with healed blaze, bears S.52°W., 43.6'
13" sawed Fir stump, 5.5 ft tall with healed blaze, bears S.50°45'W., 48.8'